

GEMÜ 567 BioStar control

Pneumatically operated control valve

EN

Operating instructions



further information
webcode: GW-567



All rights including copyrights or industrial property rights are expressly reserved.

Keep the document for future reference.

© GEMÜ Gebr. Müller Apparatebau GmbH & Co. KG
29.11.2023

Contents

1 General information	4
1.1 Information	4
1.2 Symbols used	4
1.3 Definition of terms	4
1.4 Warning notes	4
2 Safety information	5
3 Product description	5
4 Correct use	7
5 Order data	8
6 Technical data	11
6.1 Medium	11
6.2 Temperature	11
6.3 Pressure	11
6.4 Product compliance	15
6.5 Mechanical data	15
7 Dimensions	16
7.1 Actuator dimensions	16
7.2 Body dimensions	17
8 Manufacturer's information	37
8.1 Delivery	37
8.2 Packaging	37
8.3 Transport	37
8.4 Storage	37
9 Installation in piping	37
9.1 Installation location	37
9.2 Preparing for installation	37
9.3 Installation with clamp connections	38
9.4 Installation with butt weld spigots	38
10 Mounting	39
11 Commissioning	40
12 Troubleshooting	41
13 Inspection and maintenance	42
14 Removal from piping	51
15 Disposal	51
16 Returns	51
17 Declaration of Incorporation according to 2006/42/EC (Machinery Directive)	52
18 Declaration of conformity according to 2014/68/ EU (Pressure Equipment Directive)	53

1 General information

1.1 Information

- The descriptions and instructions apply to the standard versions. For special versions not described in this document the basic information contained herein applies in combination with any additional special documentation.
- Correct installation, operation, maintenance and repair work ensure faultless operation of the product.
- Should there be any doubts or misunderstandings, the German version is the authoritative document.
- Contact us at the address on the last page for staff training information.

1.2 Symbols used

The following symbols are used in this document:

Symbol	Meaning
●	Tasks to be performed
►	Response(s) to tasks
–	Lists

1.3 Definition of terms

Working medium

The medium that flows through the GEMÜ product.

PD

PD = Plug Diaphragm

1.4 Warning notes



Wherever possible, warning notes are organised according to the following scheme:


SIGNAL WORD	
Possible symbol for the specific danger	Type and source of the danger <ul style="list-style-type: none"> ► Possible consequences of non-observance. ● Measures for avoiding danger.

Warning notes are always marked with a signal word and sometimes also with a symbol for the specific danger.




The following signal words and danger levels are used:

 DANGER	
	Imminent danger! <ul style="list-style-type: none"> ► Non-observance can cause death or severe injury.
 WARNING	
	Potentially dangerous situation! <ul style="list-style-type: none"> ► Non-observance can cause death or severe injury.

 CAUTION	
	Potentially dangerous situation! <ul style="list-style-type: none"> ► Non-observance can cause moderate to light injury.

NOTICE	
	Potentially dangerous situation! <ul style="list-style-type: none"> ► Non-observance can cause damage to property.

The following symbols for the specific dangers can be used within a warning note:

Symbol	Meaning
	Danger of explosion!
	Corrosive chemicals!
	Hot plant components!

2 Safety information

The safety information in this document refers only to an individual product. Potentially dangerous conditions can arise in combination with other plant components, which need to be considered on the basis of a risk analysis. The operator is responsible for the production of the risk analysis and for compliance with the resulting precautionary measures and regional safety regulations.

The document contains fundamental safety information that must be observed during commissioning, operation and maintenance. Non-compliance with these instructions may cause:

- Personal hazard due to electrical, mechanical and chemical effects.
- Hazard to nearby equipment.
- Failure of important functions.
- Hazard to the environment due to the leakage of dangerous substances.

The safety information does not take into account:

- Unexpected incidents and events, which may occur during installation, operation and maintenance.
- Local safety regulations which must be adhered to by the operator and by any additional installation personnel.

Prior to commissioning:

1. Transport and store the product correctly.
2. Do not paint the bolts and plastic parts of the product.
3. Carry out installation and commissioning using trained personnel.
4. Provide adequate training for installation and operating personnel.
5. Ensure that the contents of the document have been fully understood by the responsible personnel.
6. Define the areas of responsibility.
7. Observe the safety data sheets.
8. Observe the safety regulations for the media used.

During operation:


9. Keep this document available at the place of use.
10. Observe the safety information.
11. Operate the product in accordance with this document.
12. Operate the product in accordance with the specifications.
13. Maintain the product correctly.
14. Do not carry out any maintenance work and repairs not described in this document without consulting the manufacturer first.

In cases of uncertainty:

15. Consult the nearest GEMÜ sales office.

3 Product description

3.1 Construction




Item	Name	Materials
1	Pneumatic actuator connection	
2	Actuator housing	1.4305
3	Distance piece	1.4404
4	Valve body with leak detection hole	1.4435, 1.4539, 2.4602, 1.4410, 1.4529
5	CONEXO RFID chip	
6	Plug diaphragm	PTFE

3.2 Description


The GEMÜ 567 BioStar Control 2/2-way diaphragm globe valve is designed for use in sterile applications. Flow rates range from 80 l/h to 63,000 l/h, depending on the version. The sealing concept of the valve is based on the GEMÜ PD design. All actuator parts (except the seals) are made from stainless steel. Normally Closed, Normally Open and Double Acting control functions are available.

3.3 Function

The product is a pneumatic 2/2-way diaphragm globe valve made of stainless steel. The GEMÜ 567 2/2-way diaphragm globe valve is designed for installation in piping systems and has been equipped with a GEMÜ PD design. Flow rates of between 80 l/h and 63 m³/h are possible, depending on the version.



3.4 PD seal system without bypass

Seal material code 4




Seal material code 5

Item	Name	Materials
1	Plug diaphragm	PTFE
2	Support ring	1.4435, 1.4539, 2.4602, 1.4410, 1.4529
3	O-ring	FKM
4	Regulating cone	1.4435, 1.4539, 2.4602, 1.4410, 1.4529
5	Plug diaphragm with regulating cone	PTFE

3.5 PD seal system with bypass

Item	Name	Materials
1	Plug diaphragm FKM, PTFE	PTFE
2	Support ring	1.4435, 1.4539, 2.4602, 1.4410, 1.4529
3	O-ring	FKM, FFKM
4	Regulating cone	1.4435, 1.4539, 2.4602, 1.4410, 1.4529
5	Bypass valve diaphragm	PTFE-EPDM, EPDM

3.6 Installation position for optimized draining




Control range

We recommend designing the valves in such a way that the control range is within an opening stroke of 20% to 90% of the control valve.

3.7 Product label

The product label is located on the actuator. Product label data (example):



The month of manufacture is encoded in the traceability number and can be obtained from GEMÜ. The product was manufactured in Germany.

4 Correct use

⚠ DANGER

Danger of explosion!

- Risk of death or severe injury
- Do **not** use the product in potentially explosive zones.

⚠ WARNING

Improper use of the product!

- Risk of severe injury or death
- Manufacturer liability and guarantee will be void.
- Only use the product in accordance with the operating conditions specified in the contract documentation and in this document.

The product is designed for installation in piping systems and for controlling a working medium.

The product is not intended for use in potentially explosive areas.

- Use the product in accordance with the technical data.

5 Order data

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

Order codes

1 Type	Code
Control valve	567
2 DN	Code
DN 8	8
DN 10	10
DN 15	15
DN 20	20
DN 25	25
DN 32	32
DN 40	40
DN 50	50
DN 65	65
3 Body configuration	Code
2-way angle body	E
2-way angle body with bypass	M
4 Connection type	Code
Spigot	
Spigot DIN	0
Spigot EN 10357 series A (formerly DIN 11850 series 2)/DIN 11866 series A	17
Spigot ASME BPE / DIN 11866 series C	59
Spigot ISO 1127/EN 10357 series C/DIN 11866 series B	60
Clamp	
Clamp DIN 32676 series B	82
Clamp DIN 32676 series A	86
Clamp ASME BPE	88
5 Valve body material	Code
1.4435 (316L), block material	41
1.4435 (BN2), block material, $\Delta Fe < 0.5\%$	43
1.4539, block material	44
2.4602, block material Alloy 22, (NiCr21Mo14W)	A3
1.4410, block material	A7
1.4529, block material	A8
6 Seal material	Code
Actuator seal PTFE / seat seal FKM	4
Actuator seal PTFE / seat seal PTFE	5
Actuator seal PTFE / seat seal FKM / bypass seal EPDM bypass diaphragm code 13	43
Actuator seal PTFE / seat seal FKM / bypass seal PTFE bypass diaphragm code 54	45
Actuator seal PTFE / seat seal FKM / bypass seal EPDM bypass diaphragm code 17	47
Actuator seal PTFE / seat seal PTFE / bypass seal PTFE bypass diaphragm code 54	55
Actuator seal PTFE / seat seal FFKM	F

6 Seal material	Code
Actuator seal PTFE / seat seal FFKM / bypass seal PTFE bypass diaphragm code 54	F5
7 Control function	Code
Normally closed (NC)	1
Normally open (NO)	2
Double acting (DA)	3
8 Actuator version	Code
Actuator size 2, pneumatically operated	2T1
Actuator size 3, pneumatically operated	3T1
Actuator size 4, pneumatically operated	4T1
Actuator size 5T1	5T1
9 Control characteristic	Code
Modified equal-percentage	G
Linear	L
10 Kv value	Code
80 l/h	AA
100 l/h	AB
160 l/h	BC
250 l/h	BD
400 l/h	BE
630 l/h	CF
1.0 m³/h	CG
1.6 m³/h	DH
2.6 m³/h	EJ
4.1 m³/h	G1
8.0 m³/h	H2
12.5 m³/h	J3
14.0 m³/h	K4
18.0 m³/h	K5
25.0 m³/h	K6
32.0 m³/h	M7
40.0 m³/h	M8
50.0 m³/h	N9
63.0 m³/h	NK
11 Bypass actuator version	Code
Pneumatically operated, normally closed, diaphragm size 8,	11
Pneumatically operated, normally open, diaphragm size 8,	12
Manually operated, with seal adjuster, diaphragm size 8,	S0

12 Special specification	Code
Ra ≤ 0.25 µm (10 µin.) for media wetted surfaces *), in accordance with DIN 11866 HE5, electropolished internal/external, *) for inner pipe diameters < 6 mm, in the spigot Ra ≤ 0.38 µm	1516
Ra ≤ 0.25 µm (10 µin.) for media wetted surfaces *), in accordance with DIN 11866 H5, mechanically polished internal, *) for inner pipe diameters < 6 mm, in the spigot Ra ≤ 0.38 µm	1527
Ra ≤ 0.4 µm (15 µin.) for media wetted surfaces, in accordance with DIN 11866 H4, mechanically polished internal	1536
Ra ≤ 0.4 µm (15 µin.) for media wetted surfaces, in accordance with DIN 11866 HE4, electropolished internal/external	1537
Ra max. 0.51 µm (20 µin.) for media wetted surfaces, in accordance with ASME BPE SF1, mechanically polished internal	SF1
Ra max. 0.38 µm (15 µin.) for media wetted surfaces, in accordance with ASME BPE SF4, electropolished internal/external	SF4
Ra max. 0.51 µm (20 µin.) for media wetted surfaces, in accordance with ASME BPE SF5, electropolished internal/external	SF5

13 Special version	Code
Special version for 3A	M
Special version for oxygen, maximum medium temperature: 60 °C, media wetted seal materials and auxiliary materials with BAM testing	S

14 CONEXO	Code
Without	
Integrated RFID chip for electronic identification and traceability	C

Order example without bypass

Ordering option	Code	Description
1 Type	567	Control valve
2 DN	15	DN 15
3 Body configuration	E	2-way angle body
4 Connection type	17	Spigot EN 10357 series A (formerly DIN 11850 series 2)/DIN 11866 series A
5 Valve body material	41	1.4435 (316L), block material
6 Seal material	5	Actuator seal PTFE / seat seal PTFE
7 Control function	1	Normally closed (NC)
8 Actuator version	2T1	Actuator size 2, pneumatically operated
9 Control characteristic	G	Modified equal-percentage
10 Kv value	G1	4.1 m³/h
11 Special specification	1536	Ra ≤ 0.4 µm (15 µin.) for media wetted surfaces, in accordance with DIN 11866 H4, mechanically polished internal
12 Special version	M	Special version for 3A
13 CONEXO	C	Integrated RFID chip for electronic identification and traceability

Order example with bypass

Ordering option	Code	Description
1 Type	567	Control valve
2 DN	15	DN 15
3 Body configuration	M	2-way angle body with bypass
4 Connection type	17	Spigot EN 10357 series A (formerly DIN 11850 series 2)/DIN 11866 series A
5 Valve body material	41	1.4435 (316L), block material
6 Seal material	55	Actuator seal PTFE / seat seal PTFE / bypass seal PTFE bypass diaphragm code 54
7 Control function	1	Normally closed (NC)
8 Actuator version	2T1	Actuator size 2, pneumatically operated
9 Control characteristic	G	Modified equal-percentage
10 Kv value	G1	4.1 m³/h
11 Bypass actuator version	S0	Manually operated, with seal adjuster, diaphragm size 8,
12 Special specification	1536	Ra ≤ 0.4 µm (15 µin.) for media wetted surfaces, in accordance with DIN 11866 H4, mechanically polished internal
13 Special version	M	Special version for 3A
14 CONEXO	C	Integrated RFID chip for electronic identification and traceability

6 Technical data

6.1 Medium

Working medium: Corrosive, inert, gaseous and liquid media which have no negative impact on the physical and chemical properties of the body and diaphragm material.

6.2 Temperature

Media temperature:

Without bypass	-10 – 160 °C
With bypass	-10 – 100 °C
Observe pressure/temperature diagram	

Sterilization temperature:

Seat seal FKM, FFKM without bypass, (code 4, F)	160 °C ¹⁾ , steam max. 30 min ²⁾
Seat seal PTFE without bypass, (code 5)	160 °C ¹⁾ , steam max. 30 min ²⁾
Seat seal FKM, FFKM	150 °C ³⁾ , max. 30 min
bypass diaphragm material EPDM, (code 43, F3)	
Seat seal FKM, FFKM	150 °C ³⁾ , max. 30 min
bypass diaphragm material PTFE/EPDM, PTFE laminated, (code 45, F5)	
Seat seal FKM, FFKM	150 °C ³⁾ , max. 30 min
bypass diaphragm material EPDM, (code 47, F7)	
Seat seal PTFE	150 °C ³⁾ , max. 30 min
bypass diaphragm material PTFE/EPDM, PTFE laminated, (code 55)	

1) The sterilization temperature is only valid for steam (saturated steam) or superheated water.

2) Longer sterilization times or continuous operation on request.

3) If the sterilization temperatures listed above are applied to the EPDM diaphragms for longer periods of time, the service life of the diaphragms will be reduced. In these cases, maintenance cycles must be adapted accordingly. This also applies to PTFE diaphragms exposed to high temperature fluctuations. The maintenance cycles must be adapted accordingly.

Ambient temperature: -10 – 60 °C


Storage temperature: 0 – 40 °C

6.3 Pressure


Operating pressure: 0 – 10 bar

All pressures are gauge pressures. Operating pressure values were determined with static operating pressure applied on one side of a closed valve. Sealing at the valve seat and atmospheric sealing is ensured for the given values.


Information on operating pressures applied on both sides and for high purity media on request.

Operating pressure:**Pressure/Temperature diagram****Control pressure:**

DN	Actuator size		Control function	Control pressure
8, 10, 15, 20	2	Control pressure with main valve actuator	1	5.0 to 7 bar
			2 + 3	max. 4.5 bar
		Control pressure with bypass actuator	1	3.5 to 7 bar
			2 + 3	max. 4.5 bar
20, 25	3	Without bypass	1	4.5 to 7 bar
			2 + 3	max. 5.5 bar
32, 40, 50	4	Without bypass	1	4.5 to 7 bar
			2 + 3	max. 5.5 bar
50, 65	5	Without bypass	1	4.5 to 7 bar
			2 + 3	max. 5.5 bar

Control pressure diagram c.f. 2 + 3**Leakage rate:****Control valve**

Seat seal	Standard	Test procedure	Leakage rate	Test medium
FKM, PTFE	DIN EN 60534-4	1	VI	Air

Kv values:**Code 17, 60, 82 and 86**

AG	Seal material code	Control characteristic	Kv value	DN 8	DN 10	DN 15	DN 20	DN 25	DN 32	DN 40	DN 50
2	4, 43, 45, 47, F, F5	GAA, LAA	80 l/h	X	X	X	-	-	-	-	-
		GAB, LAB	100 l/h	X	X	X	-	-	-	-	-
		GBC, LBC	160 l/h	X	X	X	-	-	-	-	-
		GBD, LBD	250 l/h	X	X	X	-	-	-	-	-
		GBE, LBE	400 l/h	X	X	X	-	-	-	-	-
	5, 55	GCF, LCF	630 l/h	X	X	X	-	-	-	-	-
		GCG, LCG	1.0 m³/h	-	X	X	-	-	-	-	-
		GDH, LDH	1.6 m³/h	-	X	X	-	-	-	-	-
		GEJ, LEJ	2.6 m³/h	-	-	X	-	-	-	-	-
		GG1, LG1	4.1 m³/h	-	-	X	-	-	-	-	-
3	5	GH2, LH2	8.0 m³/h	-	-	-	X	X	-	-	-
		GJ3, LJ3	12.5 m³/h	-	-	-	-	X	-	-	-
4	5	GK4, LK4	14.0 m³/h	-	-	-	-	-	X	X	-
		GK5, LK5	18.0 m³/h	-	-	-	-	-	X	X	-
		GK6, LK6	25.0 m³/h	-	-	-	-	-	X	X	-
		GM7, LM7	32.0 m³/h	-	-	-	-	-	-	X	-
		GM8, LM8	40.0 m³/h	-	-	-	-	-	-	X	-
5	5	GN9, LN9	50.0 m³/h	-	-	-	-	-	-	-	X
		GNK, LNK	63.0 m³/h	-	-	-	-	-	-	-	X

Kv values:**Code 59 and 88**

AG	Seal material code	Control characteristic	Kv value	DN 15	DN 20	DN 25	DN 40	DN 50	DN 65
2	4, 43, 45, 47, F, F5	GAA, LAA	80 l/h	X	X	-	-	-	-
		GAB, LAB	100 l/h	X	X	-	-	-	-
		GBC, LBC	160 l/h	X	X	-	-	-	-
		GBD, LBD	250 l/h	X	X	-	-	-	-
		GBE, LBE	400 l/h	X	X	-	-	-	-
	5, 55	GCF, LCF	630 l/h	X	X	-	-	-	-
		GCG, LCG	1.0 m³/h	X	X	-	-	-	-
		GDH, LDH	1.6 m³/h	X	X	-	-	-	-
		GEJ, LEJ	2.6 m³/h	-	X	-	-	-	-
		GG1, LG1	4.1 m³/h	-	X	-	-	-	-
3	5	GH2, LH2	8.0 m³/h	-	-	X	-	-	-
4	5	GK4, LK4	14.0 m³/h	-	-	-	X	X	-
		GK5, LK5	18.0 m³/h	-	-	-	X	X	-
		GK6, LK6	25.0 m³/h	-	-	-	X	X	-
		GM7, LM7	32.0 m³/h	-	-	-	-	X	-
		GM8, LM8	40.0 m³/h	-	-	-	-	X	-
5	5	GN9, LN9	50.0 m³/h	-	-	-	-	-	X
		GNK, LNK	63.0 m³/h	-	-	-	-	-	X

Kv values - Bypass (only available in AG2)				
Code	DN8	DN10	DN15	DN20
0, 17, 86	1.5 m³/h	1.8 m³/h	2.1 m³/h	-
60, 82	1.8 m³/h	2.1 m³/h	2.1 m³/h	-
59, 88	-	-	1.8 m³/h	2.1 m³/h

AG = actuator size

Kv values determined acc.to DIN EN 60534.

6.4 Product compliance


Machinery Directive:	2006/42/EC
EMC Directive:	2014/30/EU
Food:	FDA USP Class VI Regulation (EC) No. 1935/2004 Regulation (EC) No. 10/2011

6.5 Mechanical data

Weight:	Actuator	
	Actuator size 2	2.7 kg
	Actuator size 3	5.1 kg
	Actuator size 4	10.3 kg
	Actuator size 5	20.4 kg
	Valve body	
	Actuator size 2	1.6 kg
	Actuator size 3	2.8 kg
	Actuator size 4	4.3 kg
	Actuator size 5	7.6 kg

7 Dimensions

7.1 Actuator dimensions




DN	Actuator size	A	A1	A2	G	ØB	M
8, 10, 15, 20	2	170.0	69.2	53.0	G1/4	90.0	M16x1
20, 25	3	199.0	97.0	56.5	G1/4	114.0	M16x1
32, 40, 50	4	250.4	100.0	70.5	G1/4	144.0	M16x1
50, 65	5	317.8	147.5	-	G1/4	240.0	M26x1.5

Dimensions in mm

* CT = A + H1 (see body dimensions)

7.2 Body dimensions

7.2.1 Spigot without bypass code 0




AG	DN	Connection type code 0 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
2	15	A	45.0	75.0	20.0	2.0	44.0	21.0	40.5	6.5	18.0	1.5
		B	45.0	75.0	20.0	4.0	44.0	21.0	39.5	5.5	18.0	1.5
		C	45.0	75.0	20.0	6.0	44.0	21.0	38.5	4.5	18.0	1.5
		D	45.0	75.0	20.0	8.0	44.0	21.0	41.0	3.5	18.0	1.5
		E	45.0	75.0	20.0	10.0	44.0	21.0	40.0	2.5	18.0	1.5
		G	45.0	75.0	20.0	15.0	44.0	21.0	37.5	0.0	18.0	1.5
3	20	H	55.0	95.0	25.0	20.0	54.0	26.0	50.0	0.0	22.0	1.5
	25	H	55.0	95.0	25.0	20.0	54.0	26.0	50.0	2.5	28.0	1.5
		J	55.0	95.0	25.0	25.0	54.0	26.0	47.5	0.0	28.0	1.5

Dimensions in mm

AG = actuator size

1) **Connection type**
Code 0: Spigot DIN

7.2.2 Spigot without bypass code 17

AG	DN	Connection type code 17 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
2	8	A	45.0	75.0	20.0	2.0	47.5	17.5	40.5	3.0	10.0	1.0
		B	45.0	75.0	20.0	4.0	47.5	17.5	39.5	2.0	10.0	1.0
		C	45.0	75.0	20.0	6.0	47.5	17.5	38.5	1.0	10.0	1.0
	10	A	45.0	75.0	20.0	2.0	46.5	18.5	41.5	4.0	13.0	1.5
		B	45.0	75.0	20.0	4.0	46.5	18.5	40.5	3.0	13.0	1.5
		C	45.0	75.0	20.0	6.0	46.5	18.5	39.5	2.0	13.0	1.5
		D	45.0	75.0	20.0	8.0	46.5	18.5	38.5	1.0	13.0	1.5
	15	A	45.0	75.0	20.0	2.0	43.5	21.5	44.5	7.0	19.0	1.5
		B	45.0	75.0	20.0	4.0	43.5	21.5	43.5	6.0	19.0	1.5
		C	45.0	75.0	20.0	6.0	43.5	21.5	42.5	5.0	19.0	1.5
		D	45.0	75.0	20.0	8.0	43.5	21.5	41.5	4.0	19.0	1.5
		E	45.0	75.0	20.0	10.0	43.5	21.5	40.5	3.0	19.0	1.5
3	20	H	55.0	95.0	25.0	20.0	56.5	23.5	47.5	0.0	23.0	1.5
		H	55.0	95.0	25.0	20.0	53.5	26.5	50.5	3.0	29.0	1.5
		J	55.0	95.0	25.0	25.0	53.5	26.5	48.0	0.5	29.0	1.5
	25	H	55.0	95.0	25.0	25.0	53.5	26.5	48.0	0.5	29.0	1.5


Dimensions in mm

AG = actuator size

1) Connection type

Code 17: Spigot EN 10357 series A (formerly DIN 11850 series 2)/DIN 11866 series A

7.2.3 Spigot without bypass code 17




AG	DN	Connection type code 17 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
4	32	K	73.0	112.0	20.0	32.0	62.0	31.0	54.5	1.5	38.0	1.5
	40	K	73.0	112.0	20.0	32.0	60.4	32.6	53.0	3.0	41.0	1.5
		M	73.0	112.0	20.0	38.0	60.4	32.6	56.0	0.0	41.0	1.5
5	50	N	84.0	140.0	20.0	50.0	65.4	38.6	90.0	0.0	53.0	1.5

Dimensions in mm

AG = actuator size

1) Connection type

Code 17: Spigot EN 10357 series A (formerly DIN 11850 series 2)/DIN 11866 series A

7.2.4 Spigot without bypass code 59

AG	DN	Connection type code 59 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
2	15	A	45.0	75.0	20.0	2.0	46.8	18.2	41.20	3.70	12.70	1.65
		B	45.0	75.0	20.0	4.0	46.8	18.2	40.20	2.70	12.70	1.65
		C	45.0	75.0	20.0	6.0	46.8	18.2	39.20	1.70	12.70	1.65
		D	45.0	75.0	20.0	8.0	46.8	18.2	38.20	0.70	12.70	1.65
	20	A	45.0	75.0	20.0	2.0	48.6	21.4	44.38	6.88	19.05	1.65
		B	45.0	75.0	20.0	4.0	43.6	21.4	43.38	5.88	19.05	1.65
		C	45.0	75.0	20.0	6.0	43.6	21.4	42.38	4.88	19.05	1.65
		D	45.0	75.0	20.0	8.0	43.6	21.4	41.38	3.88	19.05	1.65
		E	45.0	75.0	20.0	10.0	43.6	21.4	40.38	2.88	19.05	1.65
		G	45.0	75.0	20.0	15.0	43.6	21.4	37.88	0.38	19.05	1.65
3	25	H	55.0	95.0	25.0	20.0	55.4	24.6	48.60	1.10	25.40	1.65


Dimensions in mm

AG = actuator size

1) Connection type

Code 59: Spigot ASME BPE / DIN 11866 series C

7.2.5 Spigot without bypass code 59



AG	DN	Connection type code 59 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
4	40	K	73.0	112.0	20.0	32.0	62.0	31.0	54.6	1.4	38.1	1.65
	50	K	73.0	112.0	20.0	32.0	55.6	37.4	48.25	7.75	50.8	1.65
		M	73.0	112.0	20.0	38.0	55.6	37.4	51.25	4.75	50.8	1.65
5	65	N	84.0	140.0	20.0	50.0	60.3	43.7	84.9	5.1	63.5	1.65


Dimensions in mm

AG = actuator size

1) Connection type

Code 59: Spigot ASME BPE / DIN 11866 series C

7.2.6 Spigot without bypass code 60



AG	DN	Connection type code 60 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
2	8	A	45.0	75.0	20.0	2.0	46.3	18.7	41.65	4.15	13.5	1.6
		B	45.0	75.0	20.0	4.0	46.3	18.7	40.65	3.15	13.5	1.6
		C	45.0	75.0	20.0	6.0	46.3	18.7	39.65	2.15	13.5	1.6
	10	A	45.0	75.0	20.0	2.0	44.5	20.5	43.50	6.00	17.2	1.6
		B	45.0	75.0	20.0	4.0	44.5	20.5	42.50	5.00	17.2	1.6
		C	45.0	75.0	20.0	6.0	44.5	20.5	41.50	4.00	17.2	1.6
		D	45.0	75.0	20.0	8.0	44.5	20.5	40.50	3.00	17.2	1.6
	15	A	45.0	75.0	20.0	2.0	42.4	22.6	45.55	8.05	21.3	1.6
		B	45.0	75.0	20.0	4.0	42.4	22.6	44.55	7.05	21.3	1.6
		C	45.0	75.0	20.0	6.0	42.4	22.6	43.55	6.05	21.3	1.6
		D	45.0	75.0	20.0	8.0	42.4	22.6	42.55	5.05	21.3	1.6
		E	45.0	75.0	20.0	10.0	42.4	22.6	41.55	4.05	21.3	1.6
		G	45.0	75.0	20.0	15.0	42.4	22.6	39.05	1.55	21.3	1.6
3	20	H	55.0	95.0	25.0	20.0	54.6	25.4	49.40	1.90	29.6	1.6
	25	H	55.0	95.0	25.0	20.0	54.6	28.4	52.40	4.90	33.7	2.0
		J	55.0	95.0	25.0	25.0	51.6	28.4	49.90	2.40	33.7	2.0


Dimensions in mm

AG = actuator size

1) Connection type

Code 60: Spigot ISO 1127/EN 10357 series C/DIN 11866 series B

7.2.7 Spigot without bypass code 60




AG	DN	Connection type code 60 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
4	32	K	73.0	112.0	20.0	32.0	60.8	32.8	52.8	3.2	42.4	2.0
	40	K	73.0	112.0	20.0	32.0	57.2	35.8	49.85	6.15	48.3	2.0
		M	73.0	112.0	20.0	38.0	57.2	35.8	52.85	3.15	48.3	2.0
5	50	N	84.0	140.0	20.0	50.0	62.3	41.7	93.15	3.15	60.3	2.0

Dimensions in mm

AG = actuator size

1) Connection type

Code 60: Spigot ISO 1127/EN 10357 series C/DIN 11866 series B

7.2.8 Spigot with bypass code 0

AG	DN	Connection type code 0 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
2	15	A	53.0	75.0	20.0	2.0	52.0	21.0	44.0	6.5	18.0	1.5
		B	53.0	75.0	20.0	4.0	52.0	21.0	43.0	5.5	18.0	1.5
		C	53.0	75.0	20.0	6.0	52.0	21.0	42.0	4.5	18.0	1.5
		D	53.0	75.0	20.0	8.0	52.0	21.0	41.0	3.5	18.0	1.5
		E	53.0	75.0	20.0	10.0	52.0	21.0	40.0	2.5	18.0	1.5
		G	53.0	75.0	20.0	15.0	52.0	21.0	37.5	-	18.0	1.5


Dimensions in mm

AG = actuator size

1) **Connection type**

Code 0: Spigot DIN

7.2.9 Spigot with bypass code 17



AG	DN	Connection type code 17 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
2	8	A	53.0	75.0	20.0	2.0	55.5	17.5	40.5	3.0	10.0	1.0
		B	53.0	75.0	20.0	4.0	55.5	17.5	39.5	2.0	10.0	1.0
		C	53.0	75.0	20.0	6.0	55.5	17.5	38.5	1.0	10.0	1.0
	10	A	53.0	75.0	20.0	2.0	54.5	18.5	41.5	4.0	13.0	1.5
		B	53.0	75.0	20.0	4.0	54.5	18.5	40.5	3.0	13.0	1.5
		C	53.0	75.0	20.0	6.0	54.5	18.5	39.5	2.0	13.0	1.5
		D	53.0	75.0	20.0	8.0	54.5	18.5	38.5	1.0	13.0	1.5
	15	A	53.0	75.0	20.0	2.0	51.5	21.5	44.5	7.0	19.0	1.5
		B	53.0	75.0	20.0	4.0	51.5	21.5	43.5	6.0	19.0	1.5
		C	53.0	75.0	20.0	6.0	51.5	21.5	42.5	5.0	19.0	1.5
		D	53.0	75.0	20.0	8.0	51.5	21.5	41.5	4.0	19.0	1.5
		E	53.0	75.0	20.0	10.0	51.5	21.5	40.5	3.0	19.0	1.5
		G	53.0	75.0	20.0	15.0	51.5	21.5	38.0	0.5	19.0	1.5


Dimensions in mm

AG = actuator size

1) Connection type

Code 17: Spigot EN 10357 series A (formerly DIN 11850 series 2)/DIN 11866 series A

7.2.10 Spigot with bypass code 59



AG	DN	Connection type code 59 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
2	15	A	53.0	75.0	20.0	2.0	54.8	18.2	41.20	3.70	12.70	1.65
		B	53.0	75.0	20.0	4.0	54.8	18.2	40.20	2.70	12.70	1.65
		C	53.0	75.0	20.0	6.0	54.8	18.2	39.20	1.70	12.70	1.65
		D	53.0	75.0	20.0	8.0	54.8	18.2	38.20	0.70	12.70	1.65
	20	A	53.0	75.0	20.0	2.0	51.6	21.4	44.38	3.70	12.70	1.65
		B	53.0	75.0	20.0	4.0	51.6	21.4	43.38	2.70	12.70	1.65
		C	53.0	75.0	20.0	6.0	51.6	21.4	42.38	1.70	12.70	1.65
		D	53.0	75.0	20.0	8.0	51.6	21.4	41.38	0.70	12.70	1.65
		E	53.0	75.0	20.0	10.0	51.6	21.4	40.38	2.88	19.05	1.65
		G	53.0	75.0	20.0	15.0	51.6	21.4	37.88	0.38	19.05	1.65


Dimensions in mm

AG = actuator size

1) Connection type

Code 59: Spigot ASME BPE / DIN 11866 series C

7.2.11 Spigot with bypass code 60




AG	DN	Connection type code 60 ¹⁾										
		Seat size (code)	L	□E	c	Øz	LE	H1	H2	cz	Ød	s
2	8	A	53.0	75.0	20.0	2.0	54.3	18.7	41.65	4.15	13.5	1.6
		B	53.0	75.0	20.0	4.0	54.3	18.7	40.65	3.15	13.5	1.6
		C	53.0	75.0	20.0	6.0	54.3	18.7	39.65	2.15	13.5	1.6
	10	A	53.0	75.0	20.0	2.0	52.5	20.7	43.50	6.00	17.2	1.6
		B	53.0	75.0	20.0	4.0	52.5	20.7	42.50	5.00	17.2	1.6
		C	53.0	75.0	20.0	6.0	52.5	20.5	41.50	4.00	17.2	1.6
		D	53.0	75.0	20.0	8.0	52.5	20.5	40.50	3.00	17.2	1.6
	15	A	53.0	75.0	20.0	2.0	50.4	22.6	45.55	8.05	21.3	1.6
		B	53.0	75.0	20.0	4.0	50.4	22.6	44.55	7.05	21.3	1.6
		C	53.0	75.0	20.0	6.0	50.4	22.6	43.55	6.05	21.3	1.6
		D	53.0	75.0	20.0	8.0	50.4	22.6	42.55	5.05	21.3	1.6
		E	53.0	75.0	20.0	10.0	50.4	22.6	41.55	4.05	21.3	1.6
		G	53.0	75.0	20.0	15.0	50.4	22.6	39.05	1.55	21.3	1.6

Dimensions in mm

AG = actuator size

1) Connection type

Code 60: Spigot ISO 1127/EN 10357 series C/DIN 11866 series B

7.2.12 Clamp without bypass code 82

AG	DN	Connection type code 82 ¹⁾										
		Seat size (code)	L	□E	Øz	LE1	LE2	H1	H2	cz	Ød1	Ød3
2	8	A	45.0	75.0	2.0	59.3	74.65	18.7	41.65	4.15	10.3	25.4
		B	45.0	75.0	4.0	59.3	73.65	18.7	40.65	3.15	10.3	25.4
		C	45.0	75.0	6.0	59.3	72.65	18.7	39.65	2.15	10.3	25.4
	10	A	45.0	75.0	2.0	57.5	76.50	20.5	43.50	6.00	14.0	25.4
		B	45.0	75.0	4.0	57.5	75.50	20.5	42.50	5.00	14.0	25.4
		C	45.0	75.0	6.0	57.5	74.50	20.5	41.50	4.00	14.0	25.4
		D	45.0	75.0	8.0	57.5	73.50	20.5	40.50	3.00	14.0	25.4
	15	A	45.0	75.0	2.0	55.4	78.55	22.6	45.55	8.05	18.1	50.5
		B	45.0	75.0	4.0	55.4	77.55	22.6	44.55	7.05	18.1	50.5
		C	45.0	75.0	6.0	55.4	76.55	22.6	43.55	6.05	18.1	50.5
		D	45.0	75.0	8.0	55.4	75.55	22.6	42.55	5.05	18.1	50.5
		E	45.0	75.0	10.0	55.4	74.55	22.6	41.55	4.05	18.1	50.5
		G	45.0	75.0	15.0	55.4	72.05	22.6	39.05	1.55	18.1	50.5
3	20	H	55.0	95.0	20.0	66.0	87.40	27.0	49.40	1.90	19.0	50.5
	25	H	55.0	95.0	20.0	62.6	90.40	30.4	52.40	4.90	25.0	50.5
		J	55.0	95.0	25.0	62.6	87.90	30.4	49.90	2.40	25.0	50.5


Dimensions in mm

AG = actuator size

1) Connection type

Code 82: Clamp DIN 32676 series B

7.2.13 Clamp without bypass code 82




AG	DN	Connection type code 82 ¹⁾										
		Seat size (code)	L	□E	Øz	LE1	LE2	H1	H2	cz	Ød1	Ød3
4	32	K	73.0	112.0	32.0	73.8	85.8	32.8	52.8	3.2	38.4	64.0
	40	K	73.0	112.0	32.0	70.2	82.85	35.8	49.85	6.15	44.3	64.0
		M	73.0	112.0	38.0	70.2	85.85	35.8	52.85	3.15	44.3	64.0
5	50	N	84.0	140.0	50.0	75.3	126.15	41.7	93.15	3.15	56.3	77.5

Dimensions in mm

AG = actuator size

1) Connection type

Code 82: Clamp DIN 32676 series B

7.2.14 Clamp without bypass code 86

AG	DN	Connection type code 86 ¹⁾										
		Seat size (code)	L	□E	Øz	LE1	LE2	H1	H2	cz	Ød1	Ød3
2	8	A	45.0	75.0	2.0	60.5	73.5	17.5	40.5	3.0	8.0	25.0
		B	45.0	75.0	4.0	60.5	72.5	17.5	39.5	2.0	8.0	25.0
		C	45.0	75.0	6.0	60.5	71.5	17.5	38.5	1.0	8.0	25.0
	10	A	45.0	75.0	2.0	59.5	74.5	18.5	41.5	4.0	10.0	34.0
		B	45.0	75.0	4.0	59.5	73.5	18.5	40.5	3.0	10.0	34.0
		C	45.0	75.0	6.0	59.5	72.5	18.5	39.5	2.0	10.0	34.0
		D	45.0	75.0	8.0	59.5	71.5	18.5	38.5	1.0	10.0	34.0
	15	A	45.0	75.0	2.0	56.5	77.5	21.5	44.5	7.0	16.0	34.0
		B	45.0	75.0	4.0	56.5	76.5	21.5	43.5	6.0	16.0	34.0
		C	45.0	75.0	6.0	56.5	75.5	21.5	42.5	5.0	16.0	34.0
		D	45.0	75.0	8.0	56.5	74.5	21.5	41.5	4.0	16.0	34.0
		E	45.0	75.0	10.0	56.5	73.5	21.5	40.5	3.0	16.0	34.0
		G	45.0	75.0	15.0	56.5	71.0	21.5	38.0	0.5	16.0	34.0
3	20	H	55.0	95.0	20.0	69.5	85.5	23.0	47.5	0.0	20.0	34.0
	25	H	55.0	95.0	20.0	65.0	88.0	28.1	50.0	2.5	26.0	50.5
		J	55.0	95.0	25.0	65.0	88.5	28.1	47.5	0.0	26.0	50.5


Dimensions in mm

AG = actuator size

1) Connection type

Code 86: Clamp DIN 32676 series A

7.2.15 Clamp without bypass code 86



AG	DN	Connection type code 86 ¹⁾										
		Seat size (code)	L	□E	Øz	LE1	LE2	H1	H2	cz	Ød1	Ød3
4	32	K	73.0	112.0	32.0	75.0	87.5	31.0	54.5	1.5	32.0	50.5
	40	K	73.0	112.0	32.0	73.4	86.0	32.6	53.0	3.0	38.0	50.5
		M	73.0	112.0	38.0	73.4	89.0	32.6	56.0	0.0	38.0	50.5
5	50	N	84.0	140.0	50.0	78.4	123.0	38.6	90.0	0.0	50.0	64.0


Dimensions in mm

AG = actuator size

1) Connection type

Code 86: Clamp DIN 32676 series A

7.2.16 Clamp without bypass code 88



AG	DN	Connection type code 88 ¹⁾										
		Seat size (code)	L	□E	Øz	LE1	LE2	H1	H2	cz	Ød1	Ød3
2	15	A	45.0	75.0	2.0	59.8	74.20	18.2	41.20	3.70	9.40	25.0
		B	45.0	75.0	4.0	59.8	73.20	18.2	40.20	2.70	9.40	25.0
		C	45.0	75.0	6.0	59.8	72.20	18.2	39.20	1.70	9.40	25.0
		D	45.0	75.0	8.0	59.8	71.20	18.2	38.20	0.70	9.40	25.0
	20	A	45.0	75.0	2.0	56.5	77.38	21.4	44.38	6.88	15.75	25.0
		B	45.0	75.0	4.0	56.5	76.38	21.4	43.38	5.88	15.75	25.0
		C	45.0	75.0	6.0	56.5	75.38	21.4	42.38	4.88	15.75	25.0
		D	45.0	75.0	8.0	56.5	74.38	21.4	41.38	3.88	15.75	25.0
		E	45.0	75.0	10.0	56.5	73.38	21.4	40.38	2.88	15.75	25.0
		G	45.0	75.0	15.0	56.5	70.88	21.4	37.88	0.38	15.75	25.0
3	25	H	55.0	95.0	20.0	66.8	87.60	26.3	48.60	1.10	22.10	50.5


Dimensions in mm

AG = actuator size

1) Connection type

Code 88: Clamp ASME BPE

7.2.17 Clamp without bypass code 88




AG	DN	Connection type code 88 ¹⁾										
		Seat size (code)	L	□E	Øz	LE1	LE2	H1	H2	cz	Ød1	Ød3
4	40	K	73.0	112.0	32.0	75.1	87.6	31.0	54.6	1.4	34.8	50.5
	50	K	73.0	112.0	32.0	68.7	81.25	37.4	48.25	7.75	47.5	64.0
		M	73.0	112.0	38.0	68.7	84.25	37.4	51.25	4.75	47.5	64.0
5	65	N	84.0	140.0	50.0	73.1	117.6	43.7	84.9	5.1	60.2	77.5

Dimensions in mm

AG = actuator size

1) Connection type

Code 88: Clamp ASME BPE

7.2.18 Clamp with bypass code 82

AG	DN	Connection type code 82 ¹⁾										
		Seat size (code)	L	□E	Øz	LE1	LE2	H1	H2	cz	Ød1	Ød3
2	8	A	53.0	75.0	2.0	67.3	74.65	18.7	41.65	4.15	10.3	25.4
		B	53.0	75.0	4.0	67.3	73.65	18.7	40.65	3.15	10.3	25.4
		C	53.0	75.0	6.0	67.3	72.65	18.7	39.65	2.15	10.3	25.4
	10	A	53.0	75.0	2.0	65.5	76.50	20.5	43.50	6.00	14.0	25.4
		B	53.0	75.0	4.0	65.5	75.50	20.5	42.50	5.00	14.0	25.4
		C	53.0	75.0	6.0	65.5	74.50	20.5	41.5	4.00	14.0	25.4
		D	53.0	75.0	8.0	65.5	73.50	20.5	40.5	3.00	14.0	25.4
	15	A	53.0	75.0	2.0	63.4	78.55	22.6	45.55	8.05	18.1	50.5
		B	53.0	75.0	4.0	63.4	77.55	22.6	44.55	7.05	18.1	50.5
		C	53.0	75.0	6.0	63.4	76.55	22.6	43.55	6.05	18.1	50.5
		D	53.0	75.0	8.0	63.4	75.55	22.6	42.55	5.05	18.1	50.5
		E	53.0	75.0	10.0	63.4	74.55	22.6	41.55	4.05	18.1	50.5
		G	53.0	75.0	15.0	63.4	72.05	22.6	39.05	1.55	18.1	50.5


Dimensions in mm

AG = actuator size

1) Connection type

Code 82: Clamp DIN 32676 series B

7.2.19 Clamp with bypass code 86




AG	DN	Connection type code 86 ¹⁾										
		Seat size (code)	L	□E	Øz	LE1	LE2	H1	H2	cz	Ød1	Ød3
2	8	A	53.0	75.0	2.0	68.5	73.5	17.5	40.5	3.0	8.0	25.0
		B	53.0	75.0	4.0	68.5	72.5	17.5	39.5	2.0	8.0	25.0
		C	53.0	75.0	6.0	68.5	71.5	17.5	38.5	1.0	8.0	25.0
	10	A	53.0	75.0	2.0	67.5	74.5	18.5	41.5	4.0	10.0	34.0
		B	53.0	75.0	4.0	67.5	73.5	18.5	40.5	3.0	10.0	34.0
		C	53.0	75.0	6.0	67.5	72.5	18.5	39.5	2.0	10.0	34.0
		D	53.0	75.0	8.0	67.5	71.5	18.5	38.5	1.0	10.0	34.0
	15	A	53.0	75.0	2.0	64.5	77.5	21.5	44.5	7.0	16.0	34.0
		B	53.0	75.0	4.0	64.5	76.5	21.5	43.5	6.0	16.0	34.0
		C	53.0	75.0	6.0	64.5	75.5	21.5	42.5	5.0	16.0	34.0
		D	53.0	75.0	8.0	64.5	74.5	21.5	41.5	4.0	16.0	34.0
		E	53.0	75.0	10.0	64.5	73.5	21.5	40.5	3.0	16.0	34.0
		G	53.0	75.0	15.0	64.5	71.0	21.5	38.0	0.5	16.0	34.0

Dimensions in mm

AG = actuator size

1) Connection type

Code 86: Clamp DIN 32676 series A

7.2.20 Clamp with bypass code 88

AG	DN	Connection type code 88 ¹⁾										
		Seat size (code)	L	□E	Øz	LE1	LE2	H1	H2	cz	Ød1	Ød3
2	15	A	53.0	75.0	2.0	67.8	74.20	18.2	41.20	3.70	9.40	25.0
		B	53.0	75.0	4.0	67.8	73.20	18.2	40.20	2.70	9.40	25.0
		C	53.0	75.0	6.0	67.8	72.20	18.2	39.20	1.70	9.40	25.0
		D	53.0	75.0	8.0	67.8	71.20	18.2	38.20	0.70	9.40	25.0
	20	A	53.0	75.0	2.0	64.6	77.38	21.4	44.38	6.88	15.75	25.0
		B	53.0	75.0	4.0	64.6	76.38	21.4	43.38	5.88	15.75	25.0
		C	53.0	75.0	6.0	64.6	75.38	21.4	42.38	4.88	15.75	25.0
		D	53.0	75.0	8.0	64.6	74.38	21.4	41.38	3.88	15.75	25.0
		E	53.0	75.0	10.0	64.6	73.38	21.4	40.38	2.88	15.75	25.0
		G	53.0	75.0	15.0	64.6	70.88	21.4	37.88	0.38	15.75	25.0

Dimensions in mm

AG = actuator size

1) Connection type

Code 88: Clamp ASME BPE

8 Manufacturer's information

The controller required for valve operation is not included in the scope of delivery.

8.1 Delivery

- Check that all parts are present and check for any damage immediately upon receipt.

The product's performance is tested at the factory. The scope of delivery is apparent from the dispatch documents and the design from the order number.

8.2 Packaging

The product is packaged in a cardboard box which can be recycled as paper.

8.3 Transport

1. Only transport the product by suitable means. Do not drop. Handle carefully.
2. After the installation dispose of transport packaging material according to relevant local or national disposal regulations / environmental protection laws.

8.4 Storage

1. Store the product free from dust and moisture in its original packaging.
2. Avoid UV rays and direct sunlight.
3. Do not exceed the maximum storage temperature (see chapter "Technical data").
4. Do not store solvents, chemicals, acids, fuels or similar fluids in the same room as GEMÜ products and their spare parts.

9 Installation in piping


9.1 Installation location

⚠ CAUTION


- Do not apply external force to the valve.
- Choose the installation location so that the valve cannot be used as a foothold.
- Lay the pipeline so that the valve body is protected against transverse and bending forces, and also vibrations and tension.
- Only install the valve between matching aligned pipes.

NOTICE

- Install the actuator horizontally for optimized draining.
- The flow direction of the working medium is indicated by an arrow on the valve body.



in closed and open position
Actuator horizontal



in open position
Actuator horizontal or vertical

Control range

We recommend designing the valves in such a way that the control range is within an opening stroke of 20% to 90% of the control valve.

9.2 Preparing for installation

⚠ WARNING

The equipment is subject to pressure!

- Risk of severe injury or death
- Depressurize the plant.
- Completely drain the plant.

⚠ WARNING



Corrosive chemicals!

- Risk of caustic burns
- Wear appropriate protective gear.
- Completely drain the plant.

⚠ CAUTION



Hot plant components!

- Risk of burns
- Only work on plant that has cooled down.

⚠ CAUTION

Exceeding the maximum permissible pressure!

- Damage to the product
- Provide precautionary measures against exceeding the maximum permitted pressures caused by pressure surges (water hammer).

⚠ CAUTION

Use as step!

- Damage to the product
- Risk of slipping-off
- Choose the installation location so that the product cannot be used as a foothold.
- Do not use the product as a step or a foothold.

NOTICE**Suitability of the product!**

- The product must be appropriate for the piping system operating conditions (medium, medium concentration, temperature and pressure) and the prevailing ambient conditions.

NOTICE**Tools!**

- The tools required for installation and assembly are not included in the scope of delivery.
 - Use appropriate, functional and safe tools.
1. Ensure the product is suitable for the relevant application.
 2. Check the technical data of the product and the materials.
 3. Keep appropriate tools ready.
 4. Wear appropriate protective gear, as specified in the plant operator's guidelines.
 5. Observe appropriate regulations for connections.
 6. Have installation work carried out by trained personnel.
 7. Shut off plant or plant component.
 8. Secure plant or plant component against recommissioning.
 9. Depressurize the plant or plant component.
 10. Completely drain the plant (or plant component) and let it cool down until the temperature is below the media vaporization temperature and cannot cause scalding.
 11. Correctly decontaminate, rinse and ventilate the plant or plant component.
 12. Lay piping so that the product is protected against transverse and bending forces, and also from vibrations and tension.
 13. Only install the product between matching aligned pipes (see chapters below).
 14. Please note the flow direction (see chapter "Flow direction").
 15. Please note the installation position (see chapter "Installation position").


9.3 Installation with clamp connections

Fig. 1: Clamp connection

NOTICE**Gasket and clamp**

- The gasket and clamps for clamp connections are not included in the scope of delivery.
1. Keep ready gasket and clamp.
 2. Carry out preparation for installation (see chapter "Preparing for installation").
 3. Insert the corresponding gasket between the body of the product and the pipe connection.
 4. Connect the gasket between the body of the product and the pipe connection using clamps.
 5. Re-attach or reactivate all safety and protective devices.



9.4 Installation with butt weld spigots

Fig. 2: Butt weld spigots

1. Carry out preparation for installation (see chapter "Preparing for installation").
2. Remove the actuator before welding the valve into the plant (see chapter "Removing the actuator").
3. Adhere to good welding practices!
4. Weld the body of the product in the piping.
5. Allow butt weld spigots to cool down.
6. Mount the actuator on the valve body (see chapter "Mounting the actuator").
7. Re-attach or reactivate all safety and protective devices.
8. Flush the system.


10 Mounting

Mounting the actuator on the distance piece:




1. Move actuator **A** to the open position.
2. Place actuator **A** on distance piece **11**.
3. Place washers **17** and cap nuts **18** on stud bolts **16** and position by hand.
4. Tighten the cap nuts **18** diagonally.

Actuator size	Tightening torque
2	16-20 Nm
3	30-35 Nm
4	40 Nm
5	70 Nm




Mounting the actuator and the distance piece:



- ✓ **Actuator size 4/5:** Actuator **A** in open position.
- 5. Place actuator **A** and distance piece **11** on valve body **1**.
- 6. Place washers **17** and cap nuts **18** on stud bolts **16** and position by hand.
- 7. Tighten the cap nuts **18** diagonally.

Actuator size	Tightening torque
2	16-20 Nm
3	30-35 Nm
4	40 Nm
5	70 Nm



10.1 Mounting for option with a bypass valve

10.1.1 Mounting the diaphragm

NOTICE

- **Important:** Mount the correct diaphragm that suits the valve (suitable for medium, medium concentration, temperature and pressure). The diaphragm is a wearing part. Check the technical condition and function of the diaphragm valve before commissioning and during the whole term of use. Carry out checks regularly and determine the check intervals in accordance with the conditions of use and/or the regulatory codes and provisions applicable for this application.

NOTICE


- **Important:** Incorrectly mounted diaphragm may cause valve leakage / emission of medium. In this case remove the diaphragm, check the complete valve and diaphragm and reassemble again proceeding as described above.

Diaphragm size 8:

Compressor and actuator flange seen from below:



Push-fit diaphragm:



Item	Name
1	Recess of compressor
2	Diaphragm tab
3	Fastening spigot

1. Move the actuator to the closed position.
2. Place the diaphragm with the fastening spigot in an inclined position at the recess of the compressor and push it in.

NOTICE

- **Important:** Do not use greases or lubricants!

3. Align diaphragm tab with identifying manufacturer and material in parallel to compressor weir.

10.1.2 Mounting the actuator

1. Move the actuator to the open position.
2. Position the actuator with the mounted diaphragm on the valve body.
 - ⇒ Take care to align the compressor weir and valve body weir (diaphragm size 8).
3. Tighten the fastening elements by hand.
4. Move the actuator to the closed position.
5. Fully tighten the bolts with nuts diagonally
6. Ensure that the diaphragm is compressed evenly (approx. 10-15 %, visible by an even bulge to the outside).
7. Check tightness of completely assembled valve.

NOTICE

- **Important:** Diaphragms set in the course of time. After valve disassembly / assembly check that the bolts and nuts on the body are tight and retighten if necessary (at the very latest after the first sterilisation process).

10.2 Mounting the positioner or process controller (optional)

Refer to the relevant operating instructions for mounting the optional positioner or process controller.

11 Commissioning

- ✓ The product is installed in piping.
 - ✓ The product is pneumatically connected.
1. Check the tightness and the function of the product (close and reopen the product).
 - ⇒ Harmful foreign matter has been removed.
 - ⇒ The product is ready for use.
 3. Commission the product.

12 Troubleshooting

Error	Error cause	Troubleshooting
Working medium escaping from leak detection hole	Plug diaphragm faulty	Check plug diaphragm for potential damage, replace plug diaphragm if necessary
The product does not open or does not open fully	Actuator faulty	Replace actuator cartridge, replace actuator if necessary
	Plug diaphragm incorrectly mounted	Remove actuator, check plug diaphragm mounting, replace plug diaphragm if necessary
The product is leaking downstream (does not close or does not close fully)	Operating pressure too high	Operate the product with operating pressure specified in datasheet
	Plug diaphragm incorrectly mounted	Remove actuator, check plug diaphragm mounting, correct if necessary
	Foreign matter between plug diaphragm and valve seat	Remove actuator, remove foreign matter, check plug diaphragm and valve body for damage and replace if necessary
	Plug diaphragm faulty	Check plug diaphragm for potential damage, replace plug diaphragm if necessary
The product is leaking in the passage (does not close or does not close completely).	Valve body leaking or damaged	Carry out initialisation, check valve body for damage, replace valve body if necessary.
The product is leaking between actuator and valve body	Plug diaphragm incorrectly mounted	Remove actuator, check plug diaphragm mounting, correct if necessary
	Bolting between valve body and actuator loose	Tighten bolting between valve body and actuator
	Plug diaphragm faulty	Check plug diaphragm for potential damage, replace plug diaphragm if necessary
	Actuator/valve body damaged	Replace actuator/valve body
Connection between valve body and piping leaking	Incorrect installation	Check installation of valve body in piping
	Sealing material faulty	Replace sealing material
Valve body leaking	Valve body leaking or corroded	Check valve body for damage, replace valve body if necessary

13 Inspection and maintenance

NOTICE

Exceptional maintenance work!

- Damage to the GEMÜ product
- Any maintenance work and repairs not described in these operating instructions must not be performed without consulting the manufacturer first.

The operator must carry out regular visual examination of the GEMÜ products dependent on the operating conditions and the potential danger in order to prevent leakage and damage. The product also must be disassembled and checked for wear in the corresponding intervals.

1. Have servicing and maintenance work performed by trained personnel.
2. Wear appropriate protective gear as specified in plant operator's guidelines.
3. Shut off plant or plant component.
4. Secure the plant or plant component against recommissioning.
5. Depressurize the plant or plant component.
6. Actuate GEMÜ products which are always in the same position four times a year.

13.1 Replacing the actuator

13.1.1 Remove the actuator from the distance piece.

WARNING

The equipment is subject to pressure!

- Risk of severe injury or death
- Depressurize the plant.
- Completely drain the plant.

CAUTION



Hot plant components!

- Risk of burns
- Only work on plant that has cooled down.

WARNING



Corrosive chemicals!

- Risk of caustic burns
- Wear appropriate protective gear.
- Completely drain the plant.

CAUTION

Use of incorrect spare parts!

- Damage to the GEMÜ product
- Manufacturer liability and guarantee will be void
- Use only genuine parts from GEMÜ.

NOTICE

Important:

- After disassembly, clean all parts of contamination. Take care not to damage the parts in the process. Afterwards, check parts for potential damage. If parts are damaged, replace them.


CAUTION

Valve is no longer functioning correctly

- Damaged parts are reused.
- Remove and clean all parts, check for damage and replace if necessary.

NOTICE

- The piping need not be drained when replacing the actuator, as the valve spindle is sealed by the plug diaphragm.




1. Move the actuator **A** to the open position.
2. Undo the cap nuts **18** from the stud bolts **16**.
3. Remove the washers **17**.
4. Remove the actuator **A** from the distance piece **11**.

13.1.2 Mounting the actuator on the distance piece

1. Move actuator **A** to the open position.
2. Place actuator **A** on distance piece **11**.
3. Place washers **17** and cap nuts **18** on stud bolts **16** and position by hand.
4. Tighten the cap nuts **18** diagonally.

Actuator size	Tightening torque
2	16-20 Nm
3	30-35 Nm
4	40 Nm
5	70 Nm



13.1.3 Removing the actuator with the distance piece

⚠ WARNING

The equipment is subject to pressure!

- ▶ Risk of severe injury or death
- Depressurize the plant.
- Completely drain the plant.

⚠ CAUTION



Hot plant components!

- ▶ Risk of burns
- Only work on plant that has cooled down.

⚠ WARNING



Corrosive chemicals!

- ▶ Risk of caustic burns
- Wear appropriate protective gear.
- Completely drain the plant.

⚠ CAUTION


Use of incorrect spare parts!

- ▶ Damage to the GEMÜ product
- ▶ Manufacturer liability and guarantee will be void
- Use only genuine parts from GEMÜ.

⚠ CAUTION

Valve is no longer functioning correctly

- ▶ Damaged parts are reused.
- Remove and clean all parts, check for damage and replace if necessary.




1. Undo the cap nuts **18** from the stud bolts **16**.
 2. Remove the washers **17**.
 3. Remove the actuator **A**, including the distance piece **11**, from the valve body **1**.
- ⇒ Do not damage the sealing surface!

13.1.4 Mounting the actuator with the distance piece

- ✓ **Actuator size 4/5:** Actuator **A** in open position.


1. Place actuator **A** and distance piece **11** on valve body **1**.
2. Place washers **17** and cap nuts **18** on stud bolts **16** and position by hand.
3. Tighten the cap nuts **18** diagonally.

Actuator size	Tightening torque
2	16-20 Nm
3	30-35 Nm
4	40 Nm
5	70 Nm





13.2 Replacing the regulating cone


13.2.1 Removing the regulating cone




1. Remove the actuator (see chapter "Removing the actuator from the distance piece").
2. Undo the cap nuts **18** from the stud bolts **16**.
3. Remove the washers **17**.
4. Remove the valve body **1** from the distance piece **11**.
⇒ Do not damage the sealing surfaces!



5. Position a **WAF 8** open-end wrench on the wrench surface of the valve spindle **6** (do not damage the spindle surfaces in the process).
6. Simultaneously, position a **WAF 16** open-end wrench on the support ring **20**. By counterholding both open-end wrenches, carefully release the support ring **20** with the regulating cone **3** from the valve spindle **6**.




7. Hold the support ring **20** in place and release the regulating cone **3** using the assembly tool. Do not damage the regulating cone surface in the process.




8. Remove the O-ring **4** from the regulating cone **3**.
9. Carefully remove the solvent cement from the thread on the regulating cone **3** (e.g. using a stainless steel brush).
⇒ Do not damage the regulating cone surface in the process.


13.2.2 Mounting the regulating cone




If when removing the regulating cone **3** the plug diaphragm **2**, the adjustable insert **5** and the spring washers **9** are loosened, these must be placed back in the correct position before mounting the regulating cone **3**!



1. Mount the O-ring **4** on the regulating cone **3**.




2. Wet the thread of the regulating cone **3** with suitable thread locking compound (e.g. WEICONLOCK AN 301-65).
3. Screw the regulating cone **3** into the support ring **20** until it is hand tight.




4. Hold the support ring **20** in place and secure the regulating cone **3** using the assembly tool and hand-tighten it.

⇒ Do not damage the regulating cone surface in the process.



5. Screw the support ring **20** to the valve spindle **6** and hand-tighten it.


⇒ Where necessary, wet the thread of the valve spindle **6** with suitable thread locking compound (e.g. WEICON-LOCK AN 301-65).



6. Position a **WAF 16** open-end wrench on the regulating cone **3**. Simultaneously, position a **WAF 8** open-end wrench on the wrench surface of the valve spindle **6**. By counterholding both open-end wrenches, carefully bolt the support ring **20** with the regulating cone **3** to the valve spindle **6** (tightening torque: 7-9 Nm).
7. Place the distance piece **11** onto the valve body **1**.
8. Place washers **17** and cap nuts **18** on stud bolts **16** and position by hand.
9. Tighten the cap nuts **18** diagonally.

Actuator size	Tightening torque
2	16-20 Nm
3	30-35 Nm

Actuator size	Tightening torque
4	40 Nm
5	70 Nm



13.3 Replacing the plug diaphragm (code 4)


13.3.1 Removing the plug diaphragm

⚠ CAUTION

Use of incorrect spare parts!

- Damage to the GEMÜ product
- Manufacturer liability and guarantee will be void
- Use only genuine parts from GEMÜ.


1. Remove the support ring **20** and the regulating cone **3** (see chapter "Removing the regulating cone").



2. Remove the plug diaphragm **2** from the valve spindle **6**.
3. Clean all parts and check them for potential damage.
⇒ Do not scratch or damage parts during cleaning!
4. Replace damaged parts (only use genuine parts from GEMÜ).

13.3.2 Mounting the plug diaphragm

1. Position plug diaphragm **2** at distance piece **11** via valve spindle **6**



⇒ Where necessary, wet the thread of the valve spindle **6** with suitable thread locking compound (e.g. WEICON-LOCK AN 301-65).

2. Mount the support ring **20** and the regulating cone **3** (see chapter "Mounting the regulating cone").


13.4 Replacing the plug diaphragm (code 5)

13.4.1 Removing the plug diaphragm


⚠ CAUTION

Use of incorrect spare parts!

- Damage to the GEMÜ product
- Manufacturer liability and guarantee will be void
- Use only genuine parts from GEMÜ.




1. Remove the actuator (see chapter "Removing the actuator from the distance piece").
2. Undo the cap nuts **18** from the stud bolts **16**.
3. Remove the washers **17**.
4. Remove the valve body **1** from the distance piece **11**.
⇒ Do not damage the sealing surfaces!



5. Position a **WAF 8** open-end wrench on the wrench surface of the valve spindle **6** (do not damage the spindle surfaces in the process).
6. Undo the plug diaphragm **2**.


13.4.2 Mounting the plug diaphragm



✓ **Actuator size 4/5:** Press valve spindle **6** downwards to screw in the plug diaphragm **2** completely.

1. Screw the plug diaphragm **2** to the valve spindle **6** and hand-tighten it.
2. Place the distance piece **11** onto the valve body **1**.
3. Place washers **17** and cap nuts **18** on stud bolts **16** and position by hand.
4. Tighten the cap nuts **18** diagonally.


Actuator size	Tightening torque
2	16-20 Nm
3	30-35 Nm
4	40 Nm
5	70 Nm



13.5 Replacing the bypass valve actuator

13.5.1 Removing the actuator

1. Move the actuator to the open position.
2. Loosen fastening elements between the valve body and the actuator diagonally and remove them.



3. Remove the actuator from the valve body.
4. Move the actuator to the closed position.

NOTICE

Important:

- After disassembly, clean all parts of contamination. Take care not to damage the parts in the process. Afterwards, check parts for potential damage. If parts are damaged, replace them.

13.5.2 Removing the diaphragm

NOTICE

- Before removing the diaphragm, remove the actuator, see previous chapter "Removing the actuator".

1. Pull out the diaphragm (diaphragm size 8).

NOTICE

Important:

- After disassembly, clean all parts of contamination. Take care not to damage the parts in the process. Afterwards, check parts for potential damage. If parts are damaged, replace them.

2. Use only genuine parts from GEMÜ.

13.5.3 Mounting the diaphragm

NOTICE


- **Important:** Mount the correct diaphragm that suits the valve (suitable for medium, medium concentration, temperature and pressure). The diaphragm is a wearing part. Check the technical condition and function of the diaphragm valve before commissioning and during the whole term of use. Carry out checks regularly and determine the check intervals in accordance with the conditions of use and/or the regulatory codes and provisions applicable for this application.

NOTICE


- **Important:** Incorrectly mounted diaphragm may cause valve leakage / emission of medium. In this case remove the diaphragm, check the complete valve and diaphragm and reassemble again proceeding as described above.

Diaphragm size 8:

Compressor and actuator flange seen from below:



Push-fit diaphragm:



Item	Name
1	Recess of compressor
2	Diaphragm tab
3	Fastening spigot

1. Move the actuator to the closed position.
2. Place the diaphragm with the fastening spigot in an inclined position at the recess of the compressor and push it in.

NOTICE

► **Important:** Do not use greases or lubricants!

3. Align diaphragm tab with identifying manufacturer and material in parallel to compressor weir.

13.5.4 Mounting the actuator

1. Move the actuator to the open position.
 2. Position the actuator with the mounted diaphragm on the valve body.
 - ⇒ Take care to align the compressor weir and valve body weir (diaphragm size 8).
 3. Tighten the fastening elements by hand.
 4. Move the actuator to the closed position.
 5. Fully tighten the bolts with nuts diagonally
- 1 3
4 2
6. Ensure that the diaphragm is compressed evenly (approx. 10-15 %, visible by an even bulge to the outside).
 7. Check tightness of completely assembled valve.

NOTICE


► **Important:** Diaphragms set in the course of time. After valve disassembly / assembly check that the bolts and nuts on the body are tight and retighten if necessary (at the very latest after the first sterilisation process).

13.6 Cleaning the product


- Clean the product with a damp cloth.
- Do **not** clean the product with a high pressure cleaning device.

13.7 Spare parts

13.7.1 Seal material code 4, 43, 45, 47



Item	Name	Order description
A	Actuator	9567
1	Valve body	K567
2	Plug diaphragm	567 SVS...
4	O-ring	
2	Plug diaphragm	567 SVM...
4	O-ring	
19	Assembly tool	
2	Plug diaphragm	567 SRK 4...
3	Regulating cone	
4	O-ring	
19	Assembly tool	
	Set of screws (88491207)	567 S30E 41 2

13.7.2 Seal material code 5, 55

Item	Name	Order description
A	Actuator	9567
1	Valve body	K567
2	Plug diaphragm with regulating cone	567 SRK 5...
	Set of screws (88491207)	567 S30E 41 2

14 Removal from piping

1. Remove the clamp or screw connections in reverse order to installation.
2. Remove welded or solvent cemented connections using a suitable cutting tool.
3. Observe the safety information and accident prevention regulations.

15 Disposal

1. Pay attention to adhered residual material and gas diffusion from penetrated media.
2. Dispose of all parts in accordance with the disposal regulations/environmental protection laws.

16 Returns

Legal regulations for the protection of the environment and personnel require that the completed and signed return delivery note is included with the dispatch documents. Returned goods can be processed only when this note is completed. If no return delivery note is included with the product, GEMÜ cannot process credits or repair work but will dispose of the goods at the operator's expense.

1. Clean the product.
2. Request a return delivery note from GEMÜ.
3. Complete the return delivery note.
4. Send the product with a completed return delivery note to GEMÜ.

18 Declaration of conformity according to 2014/68/EU (Pressure Equipment Directive)

EU Declaration of Conformity

in accordance with 2014/68/EU (Pressure Equipment Directive)

We, the company

GEMÜ Gebr. Müller Apparatebau GmbH & Co. KG
Fritz-Müller-Strasse 6-8
74653 Ingelfingen-Criesbach, Germany

declare that the product listed below complies with the safety requirements of the Pressure Equipment Directive 2014/68/EU.

Note for products with a nominal size \leq DN 25:

The products are developed and produced according to GEMÜ process instructions and quality standards which comply with the requirements of ISO 9001 and ISO 14001.

According to Article 4, Paragraph 3 of the Pressure Equipment Directive 2014/68/EU these products must not be identified by a CE-label.

Description of the pressure equipment:	GEMÜ 567
Notified body:	TÜV Rheinland Industrie Service GmbH
Number:	0035
Certificate no.:	01 202 926/Q-02 0036
Conformity assessment procedure:	Module H1
Technical standard used:	AD 2000

2023-11-23



Joachim Brien
Head of BU Industry



GEMÜ Gebr. Müller Apparatebau GmbH & Co. KG
Fritz-Müller-Straße 6-8, 74653 Ingelfingen-Criesbach, Germany
Phone +49 (0) 7940 1230 · info@gemue.de
www.gemu-group.com

Subject to alteration

11.2023 | 88658295