

GEMÜ C67 CleanStar

Manually operated diaphragm valve



Features

- All wetted parts made of PFA or PTFE
- High flow rate with low-stress media channelling
- Optional flow direction
- Ideally suited for corrosive media
- Metal-free design
- Optional version with ECTFE union nut
- Also available as T valve
- Clean room production, fulfils SEMI F57

Description

The ultra pure 2/2-way diaphragm valve GEMÜ C67 HPW CleanStar is manually operated. All media wetted parts are produced from PFA or PTFE (HPW version). For the HPS version, there is a choice of valve bodies made of PP-R, natural or PVDF. A seal adjuster (not with AG 4) and an optical position indicator are integrated as standard. This High Purity version of the CleanStar series complies with the strictest purity standards and boasts high chemical resistance. It can also be used with high media temperatures. As such, it is often used at the supply and distribution level in semiconductor factories.

Technical specifications

- **Media temperature :** -10 to 150 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal sizes:** DN 4 to 50
- **Body configurations:** 2/2-way bodies | T body | V valve body
- **Connection types:** Flare | Flare SpaceSaver | Nexus Connect® | Nexus Connect® SpaceSaver | PrimeLock® | PrimeLock® SpaceSaver | Spigot | Super 300 Type Pillar® SpaceSaver | Union end | Welded-on Nexus Connect®
- **Connection standards:** DIN
- **Body materials:** PFA | PP-R, natural | PVDF
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)

Technical data depends on the respective configuration



Contents

1	CleanStar product line.....	4
2	Product description.....	5
3	Designs.....	6
	GEMÜ C67 CleanStar PFA	8
4	Availability C67 PFA.....	9
4.1	Body configuration - 2/2-way body (code D)	9
4.1.1	Materials	9
4.2	Connections.....	10
4.2.1	Body configuration - 2/2-way body (code D)	10
4.2.2	Body configuration - T body (code T).....	13
5	Order data C67 PFA	14
5.1	Order data - body configuration - 2/2-way body (code D).....	14
5.2	Order data - body configuration - T body (code T)	16
6	Technical data C67 PFA	18
6.1	Medium	18
6.2	Temperature	18
6.3	Pressure	18
6.4	Product conformities	22
6.5	Mechanical data	22
7	Dimensions C67 PFA.....	23
7.1	2/2-way valves (code D).....	23
7.1.5	Nexus Connect® (code NX)	28
7.2	T body (code T)	30
7.3	Mounting dimensions	33
	GEMÜ C67 CleanStar PFA 3/5-way	34
8	Availability C67 PFA 3/5-way	35
8.1	Connections.....	35
8.2	Actuator assignments.....	35
9	Order data C67 PFA 3/5-way	36
9.1	Order codes	36
9.2	Order example	37
10	Technical data C67 PFA 3/5-way.....	38
10.1	Medium	38
10.2	Temperature	38
10.3	Pressure	38
10.4	Product conformities	41
10.5	Mechanical data	41
11	Dimensions C67 PFA 3/5-way	41
	GEMÜ C67 CleanStar PVDF	42
12	Availability C67 PVDF	43


13 Order data C67 PVDF	44
13.1 Order codes	44
13.2 Order example	44
14 Technical data C67 PVDF	45
14.1 Medium	45
14.2 Temperature	45
14.3 Pressure	45
14.4 Product conformities	46
14.5 Mechanical data	46
15 Dimensions C67 PVDF	46
15.1 Union end (code 7, 78)	46
15.2 Connection dimensions	46
15.3 Mounting dimensions	48
GEMÜ C67 CleanStar SmartLine	49
16 Availability C67 SmartLine	50
17 Order data C67 SmartLine	51
17.1 Order codes	51
17.2 Order example	51
18 Technical data C67 SmartLine	52
18.1 Medium	52
18.2 Temperature	52
18.3 Pressure	52
18.4 Product conformities	53
18.5 Mechanical data	53
19 Dimensions C67 SmartLine	54
19.1 Flare connection (code 75, 77)	54
19.2 Butt weld spigot (code 20)	55
19.3 Union end (code 78)	56
19.4 Mounting dimensions	57
20 Manufacturer's information	58
21 Accessories	58
GEMÜ CFSTFZ/CFSTNZ	58
GEMÜ 1098	58
GEMÜ FlareStar	58
GEMÜ TU	58
GEMÜ C67 STA	58

CleanStar product line



Operation				
Manual	●	●	●	●
Nominal sizes	DN 4 up to 50	DN 10 up to 15	DN 15	DN 10 up to 32
Media temperature	-10 up to 150 °C	-10 up to 150 °C	-10 up to 120 °C	-10 up to 80 °C
Connection types				
Butt weld spigot	●	-	-	●
Flare	●	●	-	●
Flare SpaceSaver	●	●	-	-
Nexus Connect®	●	-	-	-
Nexus Connect® SpaceSaver	●	-	-	-
PrimeLock®	●	-	-	-
PrimeLock® SpaceSaver	●	-	-	-
Super 300 Type Pillar® SpaceSaver	●	-	-	-
Tube spigot	●	-	-	-
Union end	-	-	●	●
Welded-on Nexus Connect®	●	-	-	-
Body materials				
PFA	●	●	-	-
PP	-	-	-	●
PVDF	-	-	●	-
Body configuration				
2/2-way bodies	●	-	●	●
T body	●	-	-	-
V valve body	-	●	-	-
Conformities				
EAC	●	●	●	●
FDA	●	●	●	●
TA Luft (German Clean Air Act)	●	●	●	●




Product description





No.	Name	Materials
1	Seal adjuster	
2	Actuator	PVDF (body)
3	Position indicator	
4	Actuator union nut	PVDF or ECTFE
5	Union nut connections	PVDF, PFA or CPFA
6	Mounting lugs	
7	Leak detection hole	
8	Valve body	PVDF or PFA
	Diaphragm (internal)	PTFE (media wetted)/EPDM

Designs

Body configurations

Body configuration	Description
2/2-way body (code D) 	The 2/2-way body is the most commonly used body configuration. Thanks to the seal created by the weir-style body, the flow direction is freely selectable. Various pipe and tube connections can be connected to the ports, whereby both connections (X and Z) have the same connection size. However, different connection sizes can also be used by attaching corresponding fittings.
T valve body (code T) 	The T body has 3 connections. The opposing connections (X and Z) are classed as main pipe, as media flows between them at all times, regardless of the position (open/closed) of the actuator. The branch (Y) is located at a 90° angle to the main pipe. The flow across this connection can be influenced via the actuator. T valves are often used when regular analyses of the medium are required. To this end, the branch (Y) is opened briefly to remove a small volume of the medium as and when necessary. T valves are often also installed in a ring main, whereby the medium from the ring main is only released via the Y connection when the actuator is in its open position.
V valve (code V) 	The V valve body has 3 connections, two of which (X and Z) can be controlled via valve seats. The following flow schemes can therefore be implemented: • Flow between X and Y, as well as between Z and Y (both actuators open) • No flow (both actuators closed) • Flow only between X and Y (one actuator open, one actuator closed) • Flow only between Z and Y (one actuator open, one actuator closed) This diaphragm valve can be configured with two pneumatic and two manual actuators. A combination of both actuator types is also possible. V valves are often used when media need to be mixed at a specific mixing ratio. However, they can also be used to establish redundant media supply or as a mixing valve.

Special versions

	Description
High Flow (code F) 	In actuator sizes 2 and 3, the 2/2-way body is also available in a so-called High Flow design. This body version has a flow-optimized weir geometry. This reduces the pressure loss and thereby facilitates a higher flow. High Flow valve bodies are often used when higher volume flows are required. The upper image shows a cross-section of a standard version without High Flow. The lower image shows a cross-section of a High Flow design (code F).
ECTFE union nut (code E) 	The central union nut, which connects the actuator to the body via a thread, can optionally be ordered in ECTFE. This design is used if the outside environment where the valve is used contains alkaline media. In conditions such as these, a central union nut made from ECTFE can offer improved mechanical and chemical resistance. The materials can be distinguished based on their colour. In comparison with the white PVDF material, ECTFE has a slightly darker colour. The material is also uniquely indicated via an arrow on the union nut.

GEMÜ C67 CleanStar PFA

Manually operated diaphragm valve with PFA valve body



Features

- All wetted parts made of PFA or PTFE
- High flow rate with low-stress media channelling
- Optional flow direction
- Ideally suited for corrosive media
- Metal-free design
- Optional version with ECTFE union nut
- Also available as T valve
- Clean room production, fulfils SEMI F57

Description

The ultra pure 2/2-way diaphragm valve GEMÜ C67 HPW CleanStar is manually operated. All media wetted parts are produced from PFA or PTFE (HPW version). For the HPS version, there is a choice of valve bodies made of PP-R, natural or PVDF. A seal adjuster (not with AG 4) and an optical position indicator are integrated as standard. This High Purity version of the CleanStar series complies with the strictest purity standards and boasts high chemical resistance. It can also be used with high media temperatures. As such, it is often used at the supply and distribution level in semiconductor factories.

Technical specifications

- **Media temperature :** -10 to 150 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal sizes:** DN 4 to 50
- **Body configurations:** 2/2-way bodies | T body
- **Connection types:** Butt weld spigot | Flare | Flare SpaceSaver | Nexus Connect® | Nexus Connect® SpaceSaver | PrimeLock® | PrimeLock® SpaceSaver | Super 300 Type Pillar® SpaceSaver | Tube spigot | Welded-on Nexus Connect®
- **Connection standards:** DIN
- **Body materials:** PFA
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)

Technical data depends on the respective configuration

Availability C67 PFA

Body configuration - 2/2-way body (code D)

Materials

International code	DN	Connection size X, Z	Connection type (code) ¹⁾		
			30	NX	73, 75, 77, PL, T3
			PFA material (code 30)		
4	4	1/4" tube	-	X	X
	10	1/4" pipe	X	-	-
6	6	3/8" tube	-	X	X
8	10	1/2" tube	-	X	X
	15	1/2" pipe	X	-	-
12	15	3/4" tube	-	X	X
	20	3/4" pipe	X	-	-
16	20	1" tube	-	X	X
	25	1" pipe	X	-	-
20	25	1 1/4" tube	-	X	X
24	40	1 1/2" pipe	X	-	-
	40	1 1/2" tube	-	X	-
32	50	2" pipe	X	-	-

1) Connection type

Code 30: Spigot – inch, for welding or solvent cementing, depending on the body material

Code 73: Flare connection with CPFA union nut

Code 75: Flare connection with PVDF union nut

Code 77: Flare connection with PFA union nut


Code NX: Nexus Connect connection with PFA union nut

Code PL: PrimeLock connection

Code T3: Tube spigot

Connections

Body configuration - 2/2-way body (code D)



Connection type Flare (code 73, 75, 77)

Actuator size (code)	Connection size (code)	SpaceSaver position			
		None	On one side Pos. X	On one side Pos. Z (code Z)	On both sides Pos. X, Z (code S)
1, 1E	4	X	On request	X	-
	6	X	On request	X	-
2, 2E	8	X	On request	X	X
	12	X	On request	X	X
3, 3E	12	X	On request	X	X
	16	X	On request	X	X
	20	X	On request	X	X

Connection type Flare (code 73, 75, 77) – High Flow design

Actuator size (code)	Connection size (code)	SpaceSaver position			
		None	On one side Pos. X	On one side Pos. Z (code Z)	On both sides Pos. X, Z (code S)
2 F, 2EF	12	X	On request	-	-
2 F, 2EF	16	X	On request	-	-
3 F, 3EF	16	X	On request	-	-
3 F, 3EF	20	X	On request	X	X

Butt weld spigot connection type (code 30)

Actuator size (code)	Connection size X, Z (code)	Butt weld spigot	
		On both sides	On one side, pos. Z
1, 1E	4	X	-
2, 2E	8	X	X
2, 2E	12	X	X
3, 3E	12	X	X
3, 3E	16	X	X
4, 4E	24	X	-
4, 4E	32	X	-

Connection type butt weld spigot (code 30) - High Flow design

Actuator size (code)	Connection size X, Z (code)	Butt weld spigot	
		On both sides	On one side, pos. Z
2 F	8	X	-
2 F	12	X	-
3 F	16	X	-

Connection type Flare in pos. X, butt weld spigot in pos. Z (code K)

Actuator size (code)	Actuator size (code)	Connection type (code)	
		73, 75, 77	30
		On one side, pos. X	On one side, pos. Z
2, 2E	8	X	X
2, 2E	12	X	X
3, 3E	12	X	X
3, 3E	16	X	X

Connection type Flare in pos. X, butt weld spigot in pos. Z (code K) – High Flow design

Actuator size (code)	Actuator size (code)	Connection type (code)	
		73, 75, 77	30
		On one side, pos. X	On one side, pos. Z
2 F, 2EF	12	X	X
2 F, 2EF	16	X	X
3 F, 3EF	16	X	X

PrimeLock® connection type (code PL)

Actuator size (code)	Connection size (code)	Pos. SpaceSaver
		Without
1, 1E	4	X
	6	X
2, 2E	8	X

PrimeLock® (code PL) connection type – High Flow design

Actuator size (code)	Connection size (code)	Pos. SpaceSaver
		Without
2 F, 2EF	12	X
	16	X
3 F, 3EF	16	X
	20	X

Connection type tube spigot (code T3)

Actuator size (code)	Connection size (code)	SpaceSaver position
		None
1, 1E	6	X
2, 2E	8	X
	12	X
3, 3E	16	X


Connection type tube spigot (code T3) – High Flow design

Actuator size (code)	Connection size (code)	SpaceSaver position
		None
3 F, 3EF	20	X

Nexus Connect® connection type (code NX) – Standard (1, 2, 3, 4), High Flow design (2F, 3F)

Actuator size (code)	Connection size	Connection		
		On both sides		
		Injected	Welded	SpaceSaver
1, 1E	1/4"	X	-	X

Actuator size (code)	Connection size X, Z	Connection		
		On both sides		
		Injected	Welded	SpaceSaver
1, 1E	3/8"	X	-	X
2, 2E	1/2"	X	-	X
	3/4"	X	-	-
2F, 2EF	3/4"	-	-	X
	1"	-	-	-
3F, 3EF	3/4"	X	-	-
	1"	X	-	X
	1 ¼"	-	X	-
3, 3E	1 ¼"	-	X	-
4, 4E	1 ½"	-	X	-

Body configuration - T body (code T)

X→Z: Main pipe
(Flow even when valve is closed)
X→Y: Branch
(Flow only when valve is open)

Flare connection type (code 73, 75, 77)

Actuator size (code)	Connection size X, Z (code)	Connection size Y (code)	Space saver position				
			Without	X	Y	Z	X, Z (code S)
1, 1E	6	4	X	-	-	-	-
	6	6	X	-	-	-	-
	8	6	X	-	-	X	-
	12	6	X	-	-	X	-
2, 2E	8	8	X	X	X	X	-
	12	8	X	X	X	X	X
	12	12	X	X	X	X	-
	16	8	X	X	-	X	X
	16	12	X	X	-	X	-
3, 3E	16	16	X	X	-	-	-
	20	8	X	-	-	X	-
	20	12	X	-	-	-	-
	20	16	X	-	-	-	-
	20	20	X	-	-	X	-

Butt weld spigot connection type (code 30)

Actuator size (code)	Connection size X, Z (code)	Connection size Y (code)	Butt weld spigot, pos. X, Y, Z	Butt weld spigot, pos. X, Z	
				Space saver, pos. Y	Flare connection, pos. Y
1, 1E	4	4	X	-	-
	8	4	X	-	-
2, 2E	8	8	X	X	-
	12	8	X	-	-
	12	8	X	-	X
	12	12	-	-	X
3, 3E	16	8	X	-	X
	16	12	X	-	-
	16	16	X	-	X

Order data C67 PFA

Order data - body configuration - 2/2-way body (code D)

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

1 Type	Code
Diaphragm valve, manually operated, plastic handwheel, seal adjuster	C67

2 SpaceSaver position	Code
Without	
Flare connection in position X, butt weld spigot in position Z	K
SpaceSaver for X+ Z position	S
SpaceSaver for Z position	Z

3 Connection size	Code
1/4", international code: 4	4
3/8", international code: 6	6
1/2", international code: 8	8
3/4", international code: 12	12
1", international code: 16	16
1 1/4", international code: 20	20
1 1/2", international code: 24	24
2", international code: 32	32

4 Housing configuration	Code
2/2-way body	D

5 Connection type	Code
Tube	
Flare connection with CPFA union nut	73
Flare connection with PVDF union nut	75
Flare connection with PFA union nut	77
Nexus Connect connection with PFA union nut	NX
PrimeLock connection	PL
Tube spigot	T3
Pipe	
Spigot – inch, for welding or solvent cementing, depending on the body material	30

6 Valve body material	Code
PFA, perfluoroalkoxy	30

7 Diaphragm material	Code
PTFE/EPDM one-piece	54
PTFE/EPDM two-piece	5M

8 Control function	Code
Manually operated	0

9 Actuator version	Code
Standard version	
Actuator size 1	1
Actuator size 2	2
Actuator size 3	3
Actuator size 4	4
Standard version with ECTFE union nut	
Actuator size 1, with ECTFE union nut	1E
Actuator size 2, with ECTFE union nut	2E
Actuator size 3, with ECTFE union nut	3E
Actuator size 4, with ECTFE-union nut, maximum operating temperature 60 °C	4E
High Flow design	
Actuator size 2 High Flow	2 F
Actuator size 3 High Flow	3 F
High Flow design with ECTFE union nut	
Actuator size 2 High Flow, with ECTFE union nut	2EF
Actuator size 3 High Flow, with ECTFE union nut	3EF

10 Type of design	Code
Without	
CleanStar with welded-on Nexus Connect fitting	2591

11 High Purity version	Code
High Purity, white	HPW

Order example

Ordering option	Code	Description
1 Type	C67	Diaphragm valve, manually operated, plastic handwheel, seal adjuster
2 SpaceSaver position	Z	SpaceSaver for Z position
3 Connection size	8	1/2", international code: 8
4 Housing configuration	D	2/2-way body
5 Connection type	75	Flare connection with PVDF union nut
6 Valve body material	30	PFA, perfluoroalkoxy
7 Diaphragm material	54	PTFE/EPDM one-piece
8 Control function	0	Manually operated
9 Actuator version	2	Actuator size 2
10 Type of design		Without
11 High Purity version	HPW	High Purity, white

Order data - body configuration - T body (code T)

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

1 Type	Code
Diaphragm valve, manually operated, plastic handwheel, seal adjuster	C67

2 SpaceSaver position	Code
Without	
SpaceSaver for Y position	Y

3 Connection size	Code
Position Y	
1/4", international code: 4	4
3/8", international code: 6	6
1/2", international code: 8	8
3/4", international code: 12	12
1", international code: 16	16
1 1/4", international code: 20	20

4 Housing configuration	Code
T body	T

5 Connection type	Code
Tube	
Flare connection with CPFA union nut	73
Flare connection with PVDF union nut	75
Flare connection with PFA union nut	77
Pipe	
Spigot – inch, for welding or solvent cementing, depending on the body material	30

6 Valve body material	Code
PFA, perfluoroalkoxy	30

7 Diaphragm material	Code
PTFE/EPDM one-piece	54

8 Control function	Code
Manually operated	0

9 Actuator version	Code
Standard version	
Actuator size 1	1
Actuator size 2	2
Actuator size 3	3
Standard version with ECTFE union nut	
Actuator size 1, with ECTFE union nut	1E
Actuator size 2, with ECTFE union nut	2E

9 Actuator version	Code
Actuator size 3, with ECTFE union nut	3E

10 SpaceSaver 2 position	Code
SpaceSaver for X position	X
SpaceSaver for Z position	Z
SpaceSaver for X+ Z position	S

11 Connection size 2	Code
Position X and Z	
1/4", international code: 4	4
3/8", international code-2: 6	6
1/2", international code-2: 8	8
3/4", international code-2: 12	12
1", international code-2: 16	16
1 1/4", international code-2: 20	20

12 Connection type, spigot 2	Code
Tube	
Flare connection with CPFA union nut	73
Flare connection with PVDF union nut	75
Flare connection with PFA union nut	77
Pipe	
Spigot – inch, for welding or solvent cementing, depending on the body material	30

13 Type of design	Code
Without	

14 High Purity version	Code
High Purity, white	HPW

Order example

Ordering option	Code	Description
1 Type	C67	Diaphragm valve, manually operated, plastic handwheel, seal adjuster
2 SpaceSaver position	Y	SpaceSaver for Y position
3 Connection size	8	1/2", international code: 8
4 Housing configuration	T	T body
5 Connection type	75	Flare connection with PVDF union nut
6 Valve body material	30	PFA, perfluoroalkoxy
7 Diaphragm material	54	PTFE/EPDM one-piece
8 Control function	0	Manually operated
9 Actuator version	2	Actuator size 2
10 SpaceSaver 2 position	Z	SpaceSaver for Z position
11 Connection size 2	8	1/2", international code-2: 8
12 Connection type, spigot 2	75	Flare connection with PVDF union nut
13 Type of design		Without
14 High Purity version	HPW	High Purity, white

Technical data C67 PFA

Medium

Working medium: Corrosive, inert, gaseous and liquid media – in particular high-purity media – which have no negative impact on the physical and chemical properties of the body and diaphragm material.

Temperature

Media temperature: PFA valve body material (code 30): -10 – 150 °C
Observe pressure/temperature diagram

Ambient temperature: 0 – 60 °C


Storage temperature: 0 – 40 °C

Pressure


Operating pressure: 0 – 6 bar
applied upstream

Pressure/temperature diagram:

Valve body material: PFA (code 30), actuator sizes 1, 2 and 3



Valve body material: PFA (code 30), actuator sizes 4, 4E



* **Note:** The temperature/pressure diagram is only an aid. The data refers to water as a working medium. A change of operating conditions or other media may result in deviations. In case of doubt, it is advisable to test the behaviour of the material under the definitive operating conditions in a test installation. Temperatures below 0 °C can have a negative influence on the actuation speed. The pressure-bearing valve bodies are designed to maintain their functionality unchanged for a theoretical time period of 25 years. Continuously rising medium temperatures would change this time period as follows:

- 24.4 years at 110 °C
- 8.2 years at 120 °C
- 3.4 years at 130 °C
- 1.4 years at 140 °C
- 1.0 year at 150 °C

Kv values:
Body configuration – 2/2-way body (code D)

Actuator size (code)	Connection size X, Z	Connection	
		On both sides	
		Tube connectors moulded on	Pipe connection
1, 1E	1/4"	4.0	15.0
	3/8"	15.0	-
2, 2E	1/2"	35.0	68.0
	3/4"	68.0	68.0
3, 3E	3/4"	68.0	126.0
	1"	158.0	175.0
	1 ¼"	170.0	-
4, 4E	1 ½ "	-	1225.0
	2"	-	1225.0

Kv values in l/min

If the 2/2-way body has a tube and pipe connection, the Kv values of the tube connection are used.

Body configuration - 2/2-way body (code D) – High Flow design

Actuator size (code)	Connection size X, Z	Connection	
		On both sides	
		Tube connectors moulded on	Pipe connection
2 F, 2EF	1/2"	-	115.0
	3/4"	115.0	115.0
	1"	123.0	123.0
3 F, 3EF	1"	316.0	316.0
	1 ¼"	325.0	-

Kv values in l/min

Body configuration – 2/2-way body (code D) – Nexus Connect® connection type (code NX)

Actuator size (code)	Connection size X, Z	Connection	
		On both sides	
		Connection welded on	SpaceSaver
1	1/4"	7.82	-
	3/8"	13.0	13.3
2	1/2"	48.1	35.2
	3/4"	66.3	-
2F	3/4"	-	110.0
3	1"	142.0	-
	1 1/4"	142.0	-
3F	1"	-	255.0
4, 4E	1 1/2"	800.0	-

Kv values in l/min

Kv values:
Body configuration - T body (code T)

Actuator size (code)	Connection size		Connection		
			On both sides at main pipe (X, Z) and branch (Y)		One side
	Main pipe X, Z	Branch Y	Tube connection	Pipe connection	Pipe/tube connection
1, 1E	1/4"	1/4"	-	17.0	-
	3/8"	1/4"	4.0	-	-
	3/8"	3/8"	13.0	-	-
	1/2"	1/4"	-	18.0	-
	1/2"	3/8"	17.0	-	-
	3/4"	3/8"	18.0	-	-
2, 2E	1/2"	1/2"	28.0	62.0	36.0
	3/4"	1/4"	-	35.0	-
	3/4"	1/2"	35.0	38.0	38.0
	3/4"	3/4"	62.0	71.0	-
	1"	1/2"	38.0	101.0	-
	1"	3/4"	71.0	-	-
3, 3E	1"	1"	137.0	135.0	145.0
	1"	1/2"	-	101.0	42.0
	1"	3/4"	-	130.0	-
	1 1/4"	1/2"	53.0	-	-
	1 1/4"	3/4"	117.0	-	-
	1 1/4"	1"	150.0	-	-
	1 1/4"	1 1/4"	170.0	-	-

At branch Y

Kv values in l/min

Vacuum:

400 mbar absolute

The service life of the valve may be affected if exposed to a greater vacuum or when valves are installed on the pump suction side.

Product conformities

Machinery Directive: 2006/42/EC

Food: FDA

EAC: The product is certified according to EAC.


Mechanical data

Flow direction: Optional

Dimensions C67 PFA

2/2-way valves (code D)

Flare connection (code 73, 75, 77)



Actuator size ¹⁾	Connection size	Pos. Space Saver ²⁾	ØB	ØB1	H	H1	L	L1	L2
1, 1E	1/4"	-	51.4	31.5	91.5	13.6	112.8	56.4	56.4
1, 1E	1/4"	Z	51.4	31.5	91.5	13.6	120.1	56.4	63.7
1, 1E	3/8"	-	51.4	31.5	91.5	13.6	114.0	57.0	57.0
1, 1E	3/8"	Z	51.4	31.5	91.5	13.6	119.4	57.0	62.4
2, 2E	1/2"	K	64.0	60.0	109.0	19.0	133.4	65.9	67.5
2, 2E	1/2"	-	64.0	60.0	109.0	16.0	131.8	65.9	65.9
2, 2E	1/2"	S	64.0	60.0	109.0	16.0	142.0	71.0	71.0
2, 2E	1/2"	Z	64.0	60.0	109.0	16.0	136.9	65.9	71.0
2, 2E	3/4"	K	64.0	60.0	109.0	19.0	134.4	66.9	67.5
2, 2E	3/4"	-	64.0	60.0	109.0	19.0	133.8	66.9	66.9
3, 3E	3/4"	K	80.0	90.0	166.5	25.0	165.9	82.9	83.0
2, 2E	3/4"	S	64.0	60.0	109.0	19.0	156.8	78.4	78.4
2, 2E	3/4"	Z	64.0	60.0	109.0	19.0	145.3	66.9	78.4
3, 3E	3/4"	-	80.0	90.0	166.5	25.0	165.8	82.9	82.9
3, 3E	1"	K	80.0	90.0	166.5	25.0	172.5	89.5	83.0
3, 3E	1"	-	80.0	90.0	166.5	25.0	179.0	89.5	89.5
3, 3E	1"	S	80.0	90.0	166.5	25.0	188.9	89.5	99.4
3, 3E	1"	Z	80.0	90.0	166.5	25.0	188.9	89.5	99.4
3, 3E	1 1/4"	-	80.0	90.0	166.5	25.0	238.4	119.2	119.2
2 F, 2EF	3/4"	-	64.0	60.0	109.0	19.0	133.8	66.9	66.9
2 F, 2EF	3/4"	S	64.0	60.0	109.0	19.0	156.8	78.4	78.4
2 F, 2EF	3/4"	Z	64.0	60.0	109.0	19.0	145.3	66.9	78.4
2 F, 2EF	1"	-	64.0	60.0	109.0	19.0	160.0	74.0	74.0
3 F, 3EF	1"	-	80.0	90.0	166.5	25.0	179.0	89.5	89.5
3 F, 3EF	1"	S	80.0	90.0	166.5	25.0	198.8	99.4	99.4
3 F, 3EF	1"	Z	80.0	90.0	166.5	25.0	188.9	89.5	99.4

Dimensions C67 PFA

Actuator size ¹⁾	Connection size	Pos. Space Saver ²⁾	ØB	ØB1	H	H1	L	L1	L2
3 F, 3EF	1¼"	-	80.0	90.0	166.5	25.0	197.4	119.2	119.2


Dimensions in mm

1) Actuator version

- Code 1: Actuator size 1
- Code 1E: Actuator size 1, with ECTFE union nut
- Code 2: Actuator size 2
- Code 2 F: Actuator size 2 High Flow
- Code 2E: Actuator size 2, with ECTFE union nut
- Code 2EF: Actuator size 2 High Flow, with ECTFE union nut
- Code 3: Actuator size 3
- Code 3 F: Actuator size 3 High Flow
- Code 3E: Actuator size 3, with ECTFE union nut
- Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

2) SpaceSaver position

- Code K: Flare connection in position X, butt weld spigot in position Z
- Code S: SpaceSaver for X+ Z position
- Code Z: SpaceSaver for Z position

Butt weld spigot (code 30)

Actuator size ¹⁾	Conne- ction size	Pos. Space Saver ²⁾	ØB	ØB1	H	H1	L	L1	L2	Spigot (A)	
										ød	ød1
1, 1E	1/4"	-	51.4	31.5	91.5	13.6	102.0	51.0	51.0	13.7	9.2
2, 2E	1/2"	-	64.0	60.0	109.0	19.0	135.0	67.5	67.5	21.3	15.8
2, 2E	3/4"	-	64.0	60.0	109.0	19.0	135.0	67.5	67.5	26.7	20.3
3, 3E	3/4"	-	80.0	90.0	166.5	25.0	166.0	83.0	83.0	26.7	20.3
3, 3E	1"	-	80.0	90.0	166.5	25.0	166.0	83.0	83.0	33.4	26.6
4	1½"	-	132.3	140.0	197.8	40.0	194.0	97.0	97.0	48.3	40.9
4	2"	-	132.3	140.0	197.8	40.0	224.0	112.0	112.0	60.3	52.3
High Flow											
2 F, 2EF	1/2"	-	64.0	60.0	109.0	19.0	135.0	67.5	67.5	21.3	15.8
2 F, 2EF	3/4"	-	64.0	60.0	109.0	19.0	135.0	67.5	67.5	26.7	20.3
2 F, 2EF	1"	-	64.0	60.0	109.0	19.0	148.0	74.0	74.0	33.4	26.6
3 F, 3EF	1"	-	80.0	90.0	166.5	25.0	166.0	83.0	83.0	33.4	26.6

Dimensions in mm


1) Actuator version

- Code 1: Actuator size 1
- Code 1E: Actuator size 1, with ECTFE union nut
- Code 2: Actuator size 2
- Code 2 F: Actuator size 2 High Flow
- Code 2E: Actuator size 2, with ECTFE union nut
- Code 2EF: Actuator size 2 High Flow, with ECTFE union nut
- Code 3: Actuator size 3
- Code 3 F: Actuator size 3 High Flow
- Code 3E: Actuator size 3, with ECTFE union nut
- Code 3EF: Actuator size 3 High Flow, with ECTFE union nut
- Code 4: Actuator size 4

2) SpaceSaver position

- Code K: Flare connection in position X, butt weld spigot in position Z
- Code S: SpaceSaver for X+ Z position
- Code Z: SpaceSaver for Z position

PrimeLock® connection (code PL)



Actuator size ¹⁾	Connection size	Pos. Space Saver ²⁾	ØB	ØB1	H	H1	L	L1	L2
1, 1E	1/4"	-	51.4	31.5	91.5	15.0	113.0	57.0	57.0
1, 1E	3/8"	-	51.4	31.5	91.5	15.0	117.0	59.0	59.0
2, 2E	1/2"	-	64.0	60.0	109.0	16.0	141.0	71.0	71.0
2 F, 2EF	3/4"	-	64.0	60.0	109.0	19.0	156.0	79.0	79.0
2 F, 2EF	1"	-	64.0	60.0	109.0	19.0	169.0	85.0	85.0
3 F, 3EF	1"	-	80.0	90.0	166.5	25.0	185.0	94.0	94.0
3 F, 3EF	1 1/4"	-	80.0	90.0	166.5	25.0	209.0	105.0	105.0


Dimensions in mm

1) Actuator version

- Code 1: Actuator size 1
- Code 1E: Actuator size 1, with ECTFE union nut
- Code 2: Actuator size 2
- Code 2 F: Actuator size 2 High Flow
- Code 2E: Actuator size 2, with ECTFE union nut
- Code 2EF: Actuator size 2 High Flow, with ECTFE union nut
- Code 3: Actuator size 3
- Code 3 F: Actuator size 3 High Flow
- Code 3E: Actuator size 3, with ECTFE union nut
- Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

2) SpaceSaver position

- Code K: Flare connection in position X, butt weld spigot in position Z
- Code S: SpaceSaver for X+ Z position
- Code Z: SpaceSaver for Z position

Tube spigot (code T3)

Actuator size ¹⁾	Connection size	Pos. Space Saver ²⁾	$\varnothing B$	$\varnothing B1$	H	$H1$	L	$L1$	$L2$	Spigot (A)	
										$\varnothing d$	$\varnothing d1$
1, 1E	3/8"	-	51.4	31.5	107.0	13.6	106.0	53.0	53.0	9.5	6.6
2, 2E	1/2"	-	64.0	60.0	120.5	16.0	122.0	61.0	61.0	12.7	9.7
2, 2E	3/4"	-	64.0	60.0	126.5	19.0	135.0	67.5	67.5	19.05	15.9
3, 3E	1"	-	80.0	90.0	166.5	25.0	165.8	82.5	82.5	25.4	22.2
2 F, 2EF	3/4"	-	64.0	60.0	126.5	19.0	135.0	67.5	67.5	19.05	15.9
2 F, 2EF	1"	-	64.0	60.0	126.5	19.0	148.0	74.0	74.0	25.4	22.2
3 F, 3EF	1"	-	80.0	90.0	166.5	25.0	165.0	82.5	82.5	25.4	22.2
3 F, 3EF	1 1/4"	-	80.0	90.0	166.5	25.0	176.0	88.0	88.0	31.75	28.2

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 1E: Actuator size 1, with ECTFE union nut

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 2E: Actuator size 2, with ECTFE union nut

Code 2EF: Actuator size 2 High Flow, with ECTFE union nut

Code 3: Actuator size 3

Code 3 F: Actuator size 3 High Flow

Code 3E: Actuator size 3, with ECTFE union nut

Code 3EF: Actuator size 3 High Flow, with ECTFE union nut


2) SpaceSaver position

Code K: Flare connection in position X, butt weld spigot in position Z

Code S: SpaceSaver for X+ Z position

Code Z: SpaceSaver for Z position

Nexus Connect® (code NX)



Nexus Connect®, welded

Actuator size ¹⁾	Connection size	SpaceSaver position ²⁾	ØB	ØB1	H	H1	L	L1	L2
1	1/4"	-	51.4	45.0	91.5	13.6	140.5	70.3	70.3
1	3/8"	-	51.4	45.0	91.5	13.6	147.7	73.9	73.9
2	1/2"	-	64.0	64.7	109.0	19.0	153.0	76.5	76.5
2	3/4"	-	64.0	64.7	109.0	19.0	179.1	89.6	89.6
2F	3/4"	-	64.0	64.7	126.5	19.0	178.4	89.2	89.2
3, 3E	1"	-	80.0	86.8	150.5	25.0	205.0	102.5	102.5
3, 3E, 3F, 3EF	1 1/4"	-	80.0	86.8	166.5	25.0	306.0	153.0	153.0
3F	1"	-	80.0	86.8	166.5	25.0	222.4	111.2	111.2
4, 4E	1 1/2"	-	132.3	153.0	349.6	40.0	378.7	189.4	189.4

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 3: Actuator size 3

Code 3E: Actuator size 3, with ECTFE union nut

Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

Code 3 F: Actuator size 3 High Flow

Code 4: Actuator size 4

Code 4E: Actuator size 4, with ECTFE-union nut, maximum operating temperature 60 °C

2) SpaceSaver position

Code S: SpaceSaver for X+ Z position

Nexus Connect[®], SpaceSaver

Actuator size ¹⁾	Connection size	SpaceSaver pos. ²⁾	ØB	ØB1	H	H1	L	L1	L2
1	3/8"	S	51.4	38.0	91.5	13.6	112.4	56.2	56.2
2	1/2"	S	64.0	64.7	109.0	16.0	131.6	65.8	65.8
2F	3/4"	S	64.0	64.7	109.0	19.0	145.1	72.6	72.6
2F	1"	S	64.0	64.7	126.5	19.0	162.0	81.0	81.0
3F	1"	S	80.0	86.8	150.5	25.0	176.3	88.2	88.2

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 3: Actuator size 3

Code 3 F: Actuator size 3 High Flow

2) SpaceSaver position

Code S: SpaceSaver for X+ Z position

Nexus Connect[®], moulded on (Standard 1, 2, 3, HighFlow design 3F)

Actuator size ¹⁾	Connection size	SpaceSaver position ²⁾	ØB	ØB1	H	H1	L	L1	L2
1, 1E	1/4"	-	51.4	38.0	107.0	13.6	98.8	49.4	49.4
1, 1E	3/8"	-	51.4	38.0	107.0	13.6	108.4	54.2	54.2
2, 2E	1/2"	-	64.0	64.7	120.5	16.0	134.9	67.5	67.5
2, 2E	3/4"	-	64.0	64.7	126.5	16.0	142.9	71.5	71.5
3F, 3EF	3/4"	-	80.0	86.8	166.5	25.0	161.6	80.8	80.8
3F, 3EF	1"	-	80.0	86.8	166.5	25.0	171.4	85.7	85.7

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 1E: Actuator size 1, with ECTFE union nut

Code 2: Actuator size 2


Code 2E: Actuator size 2, with ECTFE union nut

Code 3 F: Actuator size 3 High Flow

Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

2) SpaceSaver position

Code S: SpaceSaver for X+ Z position

T body (code T)**Flare connection (code 73, 75, 77)**

Actuator size ¹⁾	Connection size		Pos. Space Saver ²⁾		$\varnothing B$	$\varnothing B1$	H	H1	H2	L	L1	L2	L3	L4
	Pos. (X, Z)	Pos. (Y)	Pos. (X, Z)	Pos. (Y)										
1, 1E	3/8"	1/4"	-	-	51.4	31.5	114.5	19.0	23.0	115.0	57.5	57.5	67.4	84.4
1, 1E	3/8"	3/8"	-	-	51.4	31.5	114.5	19.0	23.0	115.0	57.5	57.5	68.0	85.0
1, 1E	1/2"	3/8"	-	-	51.4	31.5	114.5	19.0	23.0	120.8	60.4	60.4	68.0	85.0
1, 1E	1/2"	3/8"	Z	-	51.4	31.5	114.5	19.0	23.0	131.9	60.4	71.5	68.0	85.0
1, 1E	3/4"	3/8"	-	-	51.4	31.5	114.5	19.0	23.0	125.8	62.9	62.9	68.0	85.0
1, 1E	3/4"	3/8"	X	-	51.4	31.5	114.5	19.0	23.0	135.3	72.4	62.9	68.0	85.0
1, 1E	3/4"	3/8"	Z	-	51.4	31.5	114.5	19.0	23.0	135.3	62.9	72.4	68.0	85.0
2, 2E	1/2"	1/2"	-	-	64.0	60.0	126.5	19.0	19.0	131.8	65.9	65.9	80.4	98.4
2, 2E	1/2"	1/2"	Z	-	64.0	60.0	126.5	19.0	19.0	136.0	65.9	70.1	80.4	98.4
2, 2E	1/2"	1/2"	-	Y	64.0	60.0	126.5	19.0	19.0	131.8	65.9	65.9	85.5	103.5
2, 2E	3/4"	1/2"	-	-	64.0	60.0	126.5	19.0	19.0	133.8	66.9	66.9	80.4	98.4
2, 2E	3/4"	1/2"	S	-	64.0	60.0	126.5	19.0	19.0	156.8	78.4	78.4	80.4	98.4
2, 2E	3/4"	1/2"	X	-	64.0	60.0	126.5	19.0	19.0	145.3	66.9	78.4	80.4	98.4
2, 2E	3/4"	1/2"	Z	-	64.0	60.0	126.5	19.0	19.0	145.3	66.9	78.4	80.4	98.4
2, 2E	3/4"	1/2"	-	Y	64.0	60.0	126.5	19.0	19.0	133.8	66.9	66.9	85.5	103.5
2, 2E	3/4"	3/4"	-	-	64.0	60.0	126.5	19.0	19.0	133.8	66.9	66.9	81.4	99.4
2, 2E	3/4"	3/4"	X	-	64.0	60.0	126.5	19.0	19.0	145.3	78.4	66.9	81.4	99.4
2, 2E	3/4"	3/4"	Z	-	64.0	60.0	126.5	19.0	19.0	145.3	66.9	78.4	81.4	99.4
2, 2E	3/4"	3/4"	-	Y	64.0	60.0	126.5	19.0	19.0	133.8	66.9	66.9	92.4	110.4
3, 3E	1"	1"	-	-	80.0	90.0	166.5	25.0	25.0	168.0	84.0	84.0	110.5	133.0
3, 3E	1"	1"	X	-	80.0	90.0	166.5	25.0	25.0	177.9	93.9	84.0	110.5	133.0
3, 3E	1"	1"	Z	-	80.0	90.0	166.5	25.0	25.0	177.9	84.0	93.9	110.5	133.0
3, 3E	1 1/4"	1/2"	-	-	80.0	90.0	166.5	25.0	25.0	238.4	119.2	119.2	99.9	122.4
3, 3E	1 1/4"	1"	-	-	80.0	90.0	166.5	25.0	25.0	238.4	119.2	119.2	110.5	133.0
3, 3E	1 1/4"	1 1/4"	-	-	80.0	90.0	166.5	25.0	25.0	238.4	119.2	119.2	143.2	165.7

Actuator size ¹⁾	Connection size		Pos. Space Saver ²⁾		ØB	ØB1	H	H1	H2	L	L1	L2	L3	L4
	Pos. (X, Z)	Pos. (Y)	Pos. (X, Z)	Pos. (Y)										
2 F, 2EF	1"	1/2"	-	-	64.0	60.0	135.9	25.0	28.5	154.0	77.0	77.0	81.4	100.9
2 F, 2EF	1"	1/2"	S	-	64.0	60.0	135.9	25.0	28.5	163.8	81.9	81.9	81.4	100.9
2 F, 2EF	1"	1/2"	X	-	64.0	60.0	135.9	25.0	28.5	158.9	81.9	77.0	81.4	100.9
2 F, 2EF	1"	1/2"	Z	-	64.0	60.0	135.9	25.0	28.5	158.9	77.0	81.9	81.4	100.9
2 F, 2EF	1"	3/4"	-	-	64.0	60.0	135.9	25.0	28.5	154.0	77.0	77.0	82.4	101.9
2 F, 2EF	1"	3/4"	X	-	64.0	60.0	135.9	25.0	28.5	158.9	81.9	77.0	82.4	101.9
2 F, 2EF	1"	3/4"	Z	-	64.0	60.0	135.9	25.0	28.5	158.9	77.0	81.9	82.4	101.9
2 F, 2EF	1"	3/4"	-	Y	64.0	60.0	135.9	19.0	28.5	154.0	77.0	77.0	92.9	112.4


Dimensions in mm

1) **Actuator version**

Code 1: Actuator size 1
 Code 1E: Actuator size 1, with ECTFE union nut
 Code 2: Actuator size 2
 Code 2 F: Actuator size 2 High Flow
 Code 2E: Actuator size 2, with ECTFE union nut
 Code 2EF: Actuator size 2 High Flow, with ECTFE union nut
 Code 3: Actuator size 3
 Code 3 F: Actuator size 3 High Flow
 Code 3E: Actuator size 3, with ECTFE union nut
 Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

2) **SpaceSaver position**

Code X: SpaceSaver for X position
 Code Y: SpaceSaver for Y position
 Code Z: SpaceSaver for Z position

Butt weld spigot (code 30)

Dimensions Spigot (A) (see "Butt weld spigot (code 30)", page 25)

Actuator size ¹⁾	Connection size		Pos. Space Saver ²⁾	Con- nection ³⁾	ØB	ØB1	H	H1	H2	L	L1	L2	L3	L4
	Pos. (X, Z)	Pos. (Y)	Pos. (Y)	Pos. (Y)										
1, 1E	1/4"	1/4"	-	30	51.4	31.5	114.5	19.0	23.0	106.0	53.0	53.0	63.5	80.5
1, 1E	1/4"	1/2"	-	30	51.4	31.5	114.5	19.0	23.0	106.0	53.0	53.0	63.5	80.5
2, 2E	1/2"	1/2"	-	30	64.0	60.0	126.5	19.0	19.0	122.0	61.0	61.0	75.5	93.5
2, 2E	1/4"	3/4"	-	30	64.0	60.0	135.9	25.0	28.5	140.0	70.0	70.0	76.5	96.0
3, 3E	1/2"	1"	-	30	80.0	90.0	166.5	25.0	25.0	163.0	81.5	81.5	102.0	124.5
3, 3E	1/2"	1"	-	73, 75, 77	80.0	90.0	166.5	25.0	25.0	163.0	81.5	81.5	99.9	122.4
3, 3E	3/4"	1"	-	30	80.0	90.0	166.5	25.0	25.0	163.0	81.5	81.5	102.0	124.5
3, 3E	1"	1"	-	30	80.0	90.0	166.5	25.0	25.0	163.0	81.5	81.5	103.5	126.0
3, 3E	1"	1"	-	73, 75, 77	80.0	90.0	166.5	25.0	25.0	163.0	81.5	81.5	110.5	133.0

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 1E: Actuator size 1, with ECTFE union nut

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 2E: Actuator size 2, with ECTFE union nut

Code 2EF: Actuator size 2 High Flow, with ECTFE union nut

Code 3: Actuator size 3

Code 3 F: Actuator size 3 High Flow

Code 3E: Actuator size 3, with ECTFE union nut

Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

2) SpaceSaver position

Code X: SpaceSaver for X position

Code Y: SpaceSaver for Y position

Code Z: SpaceSaver for Z position

3) Connection type

Code 30: Spigot – inch, for welding or solvent cementing, depending on the body material


Code 73: Flare connection with CPFA union nut

Code 75: Flare connection with PVDF union nut


Code 77: Flare connection with PFA union nut

Mounting dimensions

2/2-way valve (code D)



T valve (code T)



2/2-way valves (code D)

Actuator size	ød	A	B	C
1, 1E	5.5	50.5	25.25	33.5
2, 2E, 2 F, 2EF	5.5	61.5	31.0	40.0
3, 3E, 3 F, 3EF	6.5	78.0	39.0	56.0
4, 4E	9.0	124.0	62.0	94.0


Dimensions in mm

T valve (code T)

Actuator size	ød	A	B	C
1, 1E	5.5	44.3	27.3	50.0
2, 2E, 2 F, 2EF	5.5	61.5	43.5	41.5
3, 3E, 3 F, 3EF	6.5	79.5	57.0	52.5

Dimensions in mm

Mounting holes, round and slotted hole



Dimensions in mm

Dear customers,
 In order to simplify installation, we are switching over the mounting holes to slotted holes for all valve sizes.
 Due to the gradual changeover in manufacturing, you may therefore receive valve bodies with new slotted holes and also with the old, round boreholes during this phase.
 We ask for your understanding in this matter.

GEMÜ C67 CleanStar PFA 3/5-way

Manually operated 3/5-way diaphragm valve with PFA valve body



Features

- High flow rate
- Minimal contamination
- Minimal deadleg
- Optional flow direction
- Can be used as a media mixing configuration or manifold valve
- Both actuators can be independently controlled
- Combination of manual and pneumatic actuator selectable

Description

The ultra pure 3/5-way diaphragm valve GEMÜ C67 CleanStar® with a V valve body produced from PFA has two valve seats. All media wetted parts are produced from PFA or PTFE (diaphragms). The external actuator parts are produced from PVDF. Solid mounting lugs, as well as a leak detection hole, are integrated as standard. The union nuts are available in PVDF, PFA and C-PFA. This High Purity version of the CleanStar series complies with the strictest purity standards and boasts high chemical resistance. It can also be used with high media temperatures. As such, it is often used at the supply and distribution level in semiconductor factories, particularly to collect or mix media flows.

Technical specifications

- **Media temperature :** -10 to 150 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal sizes:** DN 10 to 15
- **Body configurations:** V valve body
- **Connection types:** Flare | Flare SpaceSaver
- **Connection standards:** DIN
- **Body materials:** PFA
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)


Technical data depends on the respective configuration

Availability C67 PFA 3/5-way

Connections

Actuator size	Flare connection	SpaceSaver position					Butt weld spigot
	Connection size X, Y, Z	Without	X (code X)	Y (code Y)	Z (code Z)	X, Z (code S)	
	Code						
2	8	X	-	-	-	-	-
	12	X	-	-	-	-	-

Actuator assignments



V1		V2		Control function (code)
Valve 1 (position X - Y)		Valve 2 (position Z - Y)		
Type	Control function	Type	Control function	
C60	Normally closed (NC)	C60	Normally closed (NC)	1
C60	Normally closed (NC)	C60	Normally open (NO)	D
C60	Normally closed (NC)	C67	Manually operated	F
C60	Normally open (NO)	C60	Normally open (NO)	2
C60	Normally open (NO)	C60	Normally closed (NC)	G
C60	Normally open (NO)	C67	Manually operated	K
C67	Manually operated	C60	Normally closed (NC)	A
C67	Manually operated	C60	Normally open (NO)	B
C67	Manually operated	C67	Manually operated	0

Order data C67 PFA 3/5-way

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

Provisionally only designs with the same nominal sizes in all positions

1 Type	Code
C60 - valve 1 (between X - Y)	
Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)	C60
C67 - valve 1 (between X - Y)	
Diaphragm valve, manually operated, plastic handwheel, seal adjuster	C67

2 SpaceSaver position	Code
Without	
SpaceSaver for X+ Z position	S
SpaceSaver for X position	X
SpaceSaver for Y position	Y
SpaceSaver for Z position	Z

3 Connection size	Code
Position Y	
1/2", international code: 8	8
3/4", international code: 12	12

4 Housing configuration	Code
Multi-port body V-form	V

5 Connection type	Code
Tube	
Flare connection with CPFA union nut	73
Flare connection with PVDF union nut	75
Flare connection with PFA union nut	77

6 Valve body material	Code
PFA, perfluoroalkoxy	30

7 Diaphragm material	Code
PTFE/EPDM one-piece	54

8 Control function	Code
C60 / C60	
Normally closed (NC)	1
Normally open (NO)	2
Normally closed, normally open	D
Normally open, normally closed	G

8 Control function	Code
C60 / C67	
Normally closed, manually operated	F
Normally open, manually operated	K
C67 / C60	
Manually operated, normally closed	A
Manually operated, normally open	B
C67 / C67	
Manually operated	0

9 Actuator version	Code
Standard version	
Actuator size 2	2
Standard version with ECTFE union nut	
Actuator size 2, with ECTFE union nut	2E

10 Type of design	Code
Without	
C60, spring, PFA-coated (on request)	7030

11 SpaceSaver 2 position	Code
Without	
SpaceSaver for X+ Z position	S
SpaceSaver for X position	X
SpaceSaver for Y position	Y
SpaceSaver for Z position	Z

12 Connection size 2	Code
Position X and Z	
1/2", international code-2: 8	8
3/4", international code-2: 12	12

13 Connection type, spigot 2	Code
Position X and Z	
Tube	
Flare connection with CPFA union nut	73
Flare connection with PVDF union nut	75
Flare connection with PFA union nut	77

14 High Purity version	Code
High Purity, white	HPW

Order example

Ordering option	Code	Description
1 Type	C60	Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)
2 SpaceSaver position	Y	SpaceSaver for Y position
3 Connection size	8	1/2", international code: 8
4 Housing configuration	V	Multi-port body V-form
5 Connection type	75	Flare connection with PVDF union nut
6 Valve body material	30	PFA, perfluoroalkoxy
7 Diaphragm material	54	PTFE/EPDM one-piece
8 Control function	F	Normally closed, manually operated
9 Actuator version	2	Actuator size 2
10 Type of design		Without
11 SpaceSaver 2 position	S	SpaceSaver for X+ Z position
12 Connection size 2	8	1/2", international code-2: 8
13 Connection type	75	Flare connection with PVDF union nut
14 High Purity version	HPW	High Purity, white

Technical data C67 PFA 3/5-way

Medium

Working medium: Gaseous and liquid media (specified in the table below based on nominal size) – in particular high-purity media – which have no negative impact on the physical and chemical properties of the body and diaphragm material. Inert gases are excluded.

Categorisation

Max. permissible operating pressure (PS)	Permissible working media/fluids acc. to nominal size			
	Group 1 fluids (hazardous)		Group 2 fluids (other)	
	Gases (diagram 6)	Liquids (diagram 8)	Gases (diagram 7)	Liquids (diagram 9)
6 bar	Up to max. 1"/DN25	> 1"/DN25		

Temperature

Media temperature: PFA valve body material (code 30): -10 – 150 °C
Observe pressure/temperature diagram

Ambient temperature: 0 – 60 °C


Storage temperature: 0 – 40 °C

Pressure

Operating pressure: 0 – 6 bar
applied upstream

Pressure/temperature diagram:

Valve body material: PFA, 3/5-way (code 30), actuator size 2



* **Note:** The temperature/pressure diagram is only an aid. The data refers to water as a working medium. A change of operating conditions or other media may result in deviations. In case of doubt, it is advisable to test the behaviour of the material under the definitive operating conditions in a test installation. Temperatures below 0 °C can have a negative influence on the actuation speed. The pressure-bearing valve bodies are designed to maintain their functionality unchanged for a theoretical time period of 25 years. Continuously rising medium temperatures would change this time period as follows:

- 24.4 years at 110 °C
- 8.2 years at 120 °C
- 3.4 years at 130 °C
- 1.4 years at 140 °C
- 1.0 year at 150 °C

Kv values:

Actuator size	Body configuration	Connection size	Connection
		X, Y, Z	Tube
2	V	1/2"	28.0
		3/4"	53.0

Kv values in l/min

If the 2/2-way body has a tube and pipe connection, the Kv values of the tube connection are used.

Vacuum:

400 mbar absolute

The service life of the valve may be affected if exposed to a greater vacuum or when valves are installed on the pump suction side.


Pneumatic actuator

Control pressure:

Control function	Actuator size	Control pressure
1	2	4 - 7 bar
2	2	Max. 5 bar

Control pressure / operating pressure characteristics:

Control function 2 – normally open (NO)



Control air connection: G 1/8

Filling volume:

Actuator size	Control function	
	Normally closed (NC)	Normally open (NO)
2	29.0	42.5

Filling volume in cm³

Product conformities

Machinery Directive: 2006/42/EC

Food: FDA


EAC: The product is certified according to EAC.

Pressure Equipment Directive: Categorisation in accordance with 2014/68/EU Article 4 and Annex II
Max. category **GIP** (sound engineering practice)

Mechanical data

Flow direction: Optional

Dimensions C67 PFA 3/5-way



Dimensions in mm/inch

GEMÜ C67 CleanStar PVDF

Manually operated diaphragm valve with PVDF valve body



Features

- Ideal for high purity media (for example ultra pure water)
- High flow rate
- Minimal deadleg
- Optional flow direction
- Manufactured in cleanroom conditions
- Union end for easy radial installation and removal reduces maintenance costs

Description

Thanks to its PVDF body, the GEMÜ C67 CleanStar ultra pure 2/2-way diaphragm valve is ideally suited to ultra pure water applications. All media wetted parts are made of PVDF or PTFE (diaphragm). The external actuator parts are also made of PVDF. A seal adjuster and an optical position indicator are integrated as standard. The valve also has solid mounting lugs and a leakage sensor connection.

Technical specifications

- **Media temperature :** -10 to 120 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal size:** DN 15
- **Body configurations:** 2/2-way bodies
- **Connection types:** Union end
- **Connection standards:** DIN
- **Body materials:** PVDF
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)

Technical data depends on the respective configuration

Availability C67 PVDF

Actuator size	DN	Union end (code 7, 78)	Code
2	15	X	15

Order data C67 PVDF

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

1 Type	Code
Diaphragm valve, manually operated, plastic handwheel, seal adjuster	C67
2 DN	Code
DN 15	15
3 Body configuration	Code
2/2-way body	D
4 Connection type	Code
Union end with insert (socket) – DIN	7
Union end with insert (for IR butt welding) – DIN	78

5 Valve body material	Code
PVDF	20
6 Diaphragm material	Code
PTFE/EPDM one-piece	54
7 Control function	Code
Manually operated	0
8 Actuator version	Code
Actuator size 2	2
9 High Purity version	Code
Without	
High Purity white	HPW

Order example

Ordering option	Code	Description
1 Type	C67	Diaphragm valve, manually operated, plastic handwheel, seal adjuster
2 DN	15	DN 15
3 Body configuration	D	2/2-way body
4 Connection type	78	Union end with insert (for IR butt welding) – DIN
5 Valve body material	20	PVDF
6 Diaphragm material	54	PTFE/EPDM one-piece
7 Control function	0	Manually operated
8 Actuator version	2	Actuator size 2
9 High Purity version	HPW	High Purity white

Technical data C67 PVDF

Medium

Working medium: Corrosive, inert, gaseous and liquid media – in particular high-purity media – which have no negative impact on the physical and chemical properties of the body and diaphragm material.

Temperature

Media temperature: Valve body material PVDF (code 20): -10 – 120 °C
Observe pressure/temperature diagram

Ambient temperature: 0 – 60 °C


Storage temperature: 0 – 40 °C

Pressure

Operating pressure: 0 – 6 bar
applied upstream

Pressure/temperature diagram:

Valve body material PVDF (code 20)



*** Note:** The temperature/pressure diagram is only an aid. The data refers to water as a working medium. A change of operating conditions or other media may result in deviations. In case of doubt, it is advisable to test the behaviour of the material under the definitive operating conditions in a test installation. Temperatures below 0 °C can have a negative influence on the actuation speed. The pressure-bearing valve bodies are designed to maintain their functionality unchanged for a theoretical time period of 25 years. Continuously rising medium temperatures would change this time period as follows:

- 24.4 years at 110 °C
- 8.2 years at 120 °C
- 3.4 years at 130 °C
- 1.4 years at 140 °C
- 1.0 year at 150 °C

Kv values:

Actuator size	DN	Connection size	Connection
		Pipe	Union end
2	15	1/2"	68.0

Kv values in l/min

Vacuum: 400 mbar absolute

The service life of the valve may be affected if exposed to a greater vacuum or when valves are installed on the pump suction side.

Product conformities


- Machinery Directive:2006/42/EC
- Food:FDA
- EAC:The product is certified according to EAC.

Mechanical data

- Flow direction:Optional

Dimensions C67 PVDF

Union end (code 7, 78)




Actuator size	DN	B	H	L	L1	L2
2	15	57.0	114.0	see connection dimensions		

Dimensions in mm


Connection dimensions

Union end (code 7)



Dimensions in mm


Union end (code 78)



Dimensions in mm

Mounting dimensions

2/2-way valve (code D)




2/2-way valves (code D)

Actuator size	ød	A	B	C
2, 2E, 2 F, 2EF	5.5	61.5	31.0	40.0

Dimensions in mm

Mounting holes, round and slotted hole



Dimensions in mm

Dear customers,

In order to simplify installation, we are switching over the mounting holes to slotted holes for all valve sizes. Due to the gradual changeover in manufacturing, you may therefore receive valve bodies with new slotted holes and also with the old, round boreholes during this phase. We ask for your understanding in this matter.

GEMÜ C67 CleanStar SmartLine

Manually operated SmartLine diaphragm valve with PP valve body



Features

- Improved flow capability over PFA versions
- Affordable CleanStar type for applications with less strict requirements in terms of purity
- PTFE diaphragm
- Valve body made of PP-R natural
- Manufactured in a monitored atmosphere

Description

The GEMÜ C67 HPW CleanStar ultra pure 2/2-way diaphragm valve is manually operated. All media wetted parts are made of PP or PTFE (diaphragm). The external actuator parts are made of PVDF. This GEMÜ C67 HPW CleanStar 2/2-way diaphragm valve has a valve body made of PP and is therefore an affordable alternative to the ultra pure designs. It has been specifically developed for industrial applications with less strict purity requirements (for example solar energy industry). A seal adjuster and an optical position indicator are integrated as standard. A leakage sensor connection is provided.

Technical specifications

- **Media temperature :** -10 to 80 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal sizes:** DN 10 to 32
- **Body configurations:** 2/2-way bodies
- **Connection types:** Butt weld spigot | Flare | Union end
- **Connection standards:** DIN
- **Body materials:** PP-R, natural
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)

Technical data depends on the respective configuration

Availability C67 SmartLine

Actuator size	DN	Flare connection	Butt weld spigot		Union end	Code
			Connection size X, Z	Connection size Z		
2	10	1/2" - 1/2"	-	On request	-	8
	15	-	15 - 15	On request	-	15
	15	3/4" - 3/4"	-	On request	-	12
	20	-	20 - 20	On request	-	20
	20	1" - 1"	-	On request	-	16
	25	-	25 - 25	On request	-	25
3	20	-	20 - 20	On request	-	20
	25	1" - 1"	-	On request	-	16
	25	-	25 - 25	On request	-	25
	25	-	-	On request	25 - 25	25
	25	1 1/4" - 1 1/4"	-	On request	-	20
	32	-	32 - 32	On request	-	32

Order data C67 SmartLine

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

1 Type	Code
Diaphragm valve, manually operated, plastic handwheel, seal adjuster	C67

2 Connection size	Code
1/2", international code: 8	8
DN 15	15
3/4", international code: 12	12
DN 20	20
1", international code: 16	16
DN 25	25
1 1/4", international code: 20	20
DN 32	32

3 Housing configuration	Code
2/2-way body	D

4 Connection type	Code
Spigot for IR butt welding	20
Flare connection with PVDF union nut	75

4 Connection type	Code
Flare connection with PFA union nut	77
Union end with DIN insert (for IR butt welding)	78

5 Valve body material	Code
PP-H, grey	G5
PP-R, natural	R5

6 Diaphragm material	Code
PTFE/EPDM one-piece	54

7 Control function	Code
Manually operated	0

8 Actuator version	Code
Actuator size 2	2
Actuator size 3	3

9 High Purity version	Code
Without	
Smart Line	HPS

Order example

Ordering option	Code	Description
1 Type	C67	Diaphragm valve, manually operated, plastic handwheel, seal adjuster
2 Connection size	8	1/2", international code: 8
3 Housing configuration	D	2/2-way body
4 Connection type	78	Union end with DIN insert (for IR butt welding)
5 Valve body material	G5	PP-H, grey
6 Diaphragm material	54	PTFE/EPDM one-piece
7 Control function	0	Manually operated
8 Actuator version	2	Actuator size 2
9 High Purity version	HPS	Smart Line

Technical data C67 SmartLine

Medium

Working medium: Corrosive, inert, gaseous and liquid media – in particular high-purity media – which have no negative impact on the physical and chemical properties of the body and diaphragm material.

Temperature

Media temperature: Valve body material: PP-R, natural (code R5): -10 – 80 °C
Observe pressure/temperature diagram


Ambient temperature: 0 – 60 °C

Storage temperature: 0 – 40 °C

Pressure

Operating pressure: 0 – 6 bar
applied upstream

Pressure/temperature diagram:



*** Note:** The temperature/pressure diagram is only an aid. The data refers to water as a working medium. A change of operating conditions or other media may result in deviations. In case of doubt, it is advisable to test the behaviour of the material under the definitive operating conditions in a test installation. Temperatures below 0 °C can have a negative influence on the actuation speed. The pressure-bearing valve bodies are designed to maintain their functionality unchanged for a theoretical time period of 25 years. Continuously rising medium temperatures would change this time period as follows:

- 24.4 years at 110 °C
- 8.2 years at 120 °C
- 3.4 years at 130 °C
- 1.4 years at 140 °C
- 1.0 year at 150 °C

Kv values:

Actuator size	Connection size	DN	Connection type	Connection	
	X, Z		Code	Tube	Pipe
2	1/2"	10	75, 77	34.2	-
		15	20	-	82.5
	3/4"	15	75	86.7	-
		20	20	-	83.7
		20	20	-	171.7
3	1"	20	75, 77	93.3	-
		25	20	-	94.0
		20	75, 77	183.3	-
		25	20	-	233.3
		25	78	-	233.3
	1 1/4"	25	75, 77	238.3	-
		32	20	-	238.3

Kv values in l/min

Vacuum:


400 mbar absolute

The service life of the valve may be affected if exposed to a greater vacuum or when valves are installed on the pump suction side.

Product conformities**Machinery Directive:** 2006/42/EC**Food:** FDA**EAC:** The product is certified according to EAC.**Mechanical data****Flow direction:** Optional

Dimensions C67 SmartLine


Flare connection (code 75, 77)



Actuator size	Connection size	ØB	ØB1	H	H1	L	L1	L2
2	1/2"	64.0	60.0	120.5	16.0	131.8	65.9	65.9
	3/4"	64.0	60.0	124.5	19.0	133.8	66.9	66.9
	1"	64.0	60.0	124.5	25.0	160.0	80.0	80.0
3	1"	80.0	90.0	160.5	25.0	180.0	90.0	90.0
	1 1/4"	80.0	90.0	160.5	25.0	192.0	96.0	96.0

Dimensions in mm


Butt weld spigot (code 20)



Actuator size	Conne- ction size	$\varnothing B$	$\varnothing B1$	H	H1	L	L1	L2	Spigot (A)	
									$\varnothing d$	$\varnothing d1$
2	15	64.0	60.0	124.5	19.0	131.0	65.5	65.5	20.0	16.2
	20	64.0	60.0	124.5	19.0	131.0	65.5	65.5	25.0	20.4
	25	64.0	60.0	124.5	19.0	145.0	72.5	72.5	32.0	26.0
3	20	80.0	90.0	160.5	25.0	166.0	83.0	83.0	25.0	20.4
	25	80.0	90.0	160.5	25.0	166.0	83.0	83.0	32.0	26.0
	32	80.0	90.0	160.5	25.0	172.0	86.0	86.0	40.0	32.6

Dimensions in mm


Union end (code 78)



Dimensions in mm/inch

Mounting dimensions

2/2-way valve (code D)




2/2-way valves (code D)

Actuator size	ød	A	B	C
2, 2E, 2 F, 2EF	5.5	61.5	31.0	40.0
3, 3E, 3 F, 3EF	6.5	78.0	39.0	56.0

Dimensions in mm

Mounting holes, round and slotted hole



Dimensions in mm

Dear customers,

In order to simplify installation, we are switching over the mounting holes to slotted holes for all valve sizes. Due to the gradual changeover in manufacturing, you may therefore receive valve bodies with new slotted holes and also with the old, round boreholes during this phase. We ask for your understanding in this matter.

Manufacturer's information

Accessories



GEMÜ CFSTFZ/CFSTNZ

Service tool for flare union nuts (CFSTFZ) or Nexus Connect union nuts (CFSTNZ)

This service tool is designed for fitting flare union nuts or Nexus Connect® union nuts in all available materials. To use the CFSTFZ service tool, a torque wrench is also required to fit the flare connection. The CFSTNZ service tool applies the required torque via an integrated mechanism.



GEMÜ 1098

Flaring mandrel

The flaring mandrel GEMÜ 1098 is an assembly tool for flare connections or Nexus Connect® connections.



GEMÜ FlareStar

PFA fittings

Over 1,000 different types of fitting are produced under cleanroom conditions in compliance with DIN 16901-140. The fitting bodies are made of PFA, while the union nuts are made of PFA, PVDF or CPFA. We can also supply all standard market connections.



GEMÜ TU

PFA tubing

The GEMÜ TU product range comprises ultra pure and standard PFA tubing, which is the preferred option for applications with high-purity media and other chemicals.



GEMÜ C67 STA

Service tool for actuators

Service tool for installation and removal of the central union nut.



GEMÜ Gebr. Müller Apparatebau GmbH & Co. KG
Gert-Müller-Platz 1, 74635 Kupferzell, Germany
Phone +49 (0) 7940 1230 · info@gemu.de
www.gemu-group.com